

EUROLUB KÜHLERSCHUTZ DD-40

Kühlerschutz DD-40 is a radiator protection based on ethylene glycol and glycerin. It contains an inhibitor package based on silicate and salts of organic acids (Si-OAT coolant). It is nitrite, amine, phosphate and borate free. Kühlerschutz DD-40 must be diluted with water before use.

Produkteigenschaften: Anwendung:	Kühlerschutz DD-40 protects all modern engines, especially heavy-duty aluminum engines, excellent against frost, rust and overheating. It prevents corrosion and deposition in the cooling system with the important components. Since the special application advantages of the Kühlerschutz DD-40, such as good aluminum protection and longer intervals (according to the manufacturer!), are only achieved when the Kühlerschutz DD-40 is used alone, mixing with other radiator protection agents is not recommended.
---	--

Can be used for:	VW TL 774 Ausf. J (approved for all vehicle brands of the VW Group) ASTM D 3306 CUNA NC 956-16 BS 6580: 2010
-------------------------	--

Delivery:	Art.-Nr. 838015	12 x 1,5 Liter	plastic bottle
	Art.-Nr. 838020	20 Liter	plastic can
	Art.-Nr. 838060	60 Liter	hobbock
	Art.-Nr. 838208	208 Liter	drum
	Art.-Nr. 838100	1.000 Liter	IBC

Water mixtures:
(Do not mix below -20 °C, since less than 33% Antifreeze no corrosion protection is guaranteed.)

Ratio antifreeze	Ratio water	Frost protection to:
1 part	2 parts	-20°C
1 part	1,5 parts	-27°C
1 part	1 part	-37°C

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	print: 02.01.2019, made 02.01.2019
	Referenz: gg40_0118
	Name: Kühlerschutz DD-40 PDS_english_838xxx
	Seite 1 von 1