

## EUROLUB Central Hydraulik-Fluid

<b>Description/Applications:</b>	CHF has been developed specifically for use in central hydraulic systems, power steering systems, sun roof mechanisms, hydro-pneumatic suspension systems and shock absorbers. Its first-rate viscosity-temperature behaviour guarantees safe operation at high steady-state temperatures, as well as a sensitive response at very low temperatures. Color: green
----------------------------------	--

<b>Can be used with:</b>	DIN 51524-T3 MB 343.0	ISO 7308
--------------------------	--------------------------	----------

<b>Delivery:</b>	Art.-Nr. 544001	12 x 1 Liter	bottle
	Art.-Nr. 544020	20 Liter	can
	Art.-Nr. 544060	60 Liter	hobbock
	Art.-Nr. 544208	208 Liter	drum
	Art.-Nr. 544100	Container	IBC

### Technical Data:

Data	Unit	Method	EUROLUB CHF
Density at 15°C	kg/L	D 4052	0,87
Viscosity at 40°C	cSt	D 445	21,0
Viscosity at 100°C	cSt	D 445	6,2
Viscosityindex (VI)		D 2270	280
Flash point (COC)	°C	D 92	130
Pourpoint	°C	D 6892	-51

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.