

EUROLUB HD 4C SAE 10W

Description/Applications:	<p>HD 4C 10W is a general-purpose high-performance monograde oil. The range of services covers the requirements of Diesel engines with and without turbocharging and petrol engines with appropriate instruction.</p> <p>HD 4C 10W is suitable for use in commercial vehicle diesel engines of fleets, agricultural and construction aggregates.</p> <p>It can be used in hydraulic clutches, transmissions, converter gear transmissions and retarders as hydraulic oil.</p>
----------------------------------	---

Can be used with:	<p>ACEA E2 API SJ / CF-4 MB 227.0 / 228.0 MAN 270</p>
--------------------------	---

Delivery:	<table> <tr> <td>Art.-Nr. 331020</td> <td>20 Liter</td> <td>canister</td> </tr> <tr> <td>Art.-Nr. 331060</td> <td>60 Liter</td> <td>hobbock</td> </tr> <tr> <td>Art.-Nr. 331208</td> <td>208 Liter</td> <td>Drum</td> </tr> <tr> <td>Art.-Nr. 331100</td> <td>Container</td> <td>800 – 3.000 Liter per destination</td> </tr> </table>	Art.-Nr. 331020	20 Liter	canister	Art.-Nr. 331060	60 Liter	hobbock	Art.-Nr. 331208	208 Liter	Drum	Art.-Nr. 331100	Container	800 – 3.000 Liter per destination
Art.-Nr. 331020	20 Liter	canister											
Art.-Nr. 331060	60 Liter	hobbock											
Art.-Nr. 331208	208 Liter	Drum											
Art.-Nr. 331100	Container	800 – 3.000 Liter per destination											

Technical data:			
Data:	Unit:	Method:	EUROLUB HD 4C 10W
Density at 15°C	Kg/l	DIN EN ISO 12185	0,860
Viscosity at 40°C	mm ² /s	DIN 51 562-1	41,6
Viscosity at 100°C	mm ² /s	DIN 51 562-1	7,07
Flash point (COC)	°C	DIN ISO 2592	>220
Pourpoint	°C	DIN ISO 3016	-30

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 www.eurolub.de , info@eurolub.de	print 21.11.2018, made 20.11.2018
	Referenz: pusnyd, 07/18
	Name: HD 4C SAE 10W PDS_english_331xxx
	Seite 1 von 1