

EUROLUB CLP ISO-VG 320

Category:	Industrial gear oil		
Application:	CLP is formulated with excellent base oils and state-of-the-art additive technology. Effective ingredients ensure optimum lubrication and long-lasting protection against aging. Gear oils are used to lubricate face, bevel and worm gears, gear drives and bearings with immersion and recirculating lubrication, as well as for jaw clutches, thrust bearings of roll necks and highly loaded sliding surfaces (joints).		
Can be used with_	DIN 51 517 / part 3 FZG-Test A8, 3/90 Schadenskraftstufe: >12 AIST 224 (US Steel) AGMA 9005 E02 (EP)		
Delivery:	Art.-Nr. 416020	20 Liter	plastic canister
	Art.-Nr. 416060	60 Liter	Hobbock
	Art.-Nr. 416208	208 Liter	Drum
	Art.-Nr. 416100	Container	800 – 3.000 Liter per Destination

Technical Data:			
Data	Unit	Method	EUROLUB CLP ISO-VG 320
Density at 15°C	g/cm ³	DIN 51 757	0,895
Viscosity at 40°C	mm ² /s	DIN 51 562	307,2
Viscosity at 100°C	mm ² /s	DIN 51 562	24,7
Flash point (COC)	°C	DIN ISO 2592	240
Pourpoint	°C	DIN ISO 3016	-24

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 www.eurolub.de , info@eurolub.de	print: 12.12.2018, made 12.12.2018
	Referenz: peclp, 1217
	Name: CLP 320 PDS_english_416xxx
	Seite 1 von 1