

EUROLUB HLP 22

Category: HLP Hydraulic Fluids

**Product Features:
application:** The HLP hydraulic oils is based on paraffinic base oil and modern additive technology. Effective zinc containing components guarantee optimal lubrication and long term protection against oxidation. During the process fine filtration is possible without the risk of losing valuable ingredients. Because of the high viscosity index the lubricating effect of the oil remains unaffected even at very high temperatures.

Recommendations:

DIN 51 524 / part 2	FZG-Test A8, 3/90 load stage: 12
ISO VG 22	
ISO 11158	AIST 127 + 136
ASTM D 6158	SAE MS 1004
JCMAS P041 HK	GM LS 2

Delivery:

Art.-Nr. 502020	20 Liter	plastic-canister
Art.-Nr. 502060	60 Liter	hobbock
Art.-Nr. 502208	208 Liter	Drum
Art.-Nr. 502100	Container	800 – 3.000 Liter per destination

Technical Data:

Data	Unit	Method	EUROLUB HLP 22
Density at 15°C	kg/L	ASTM D 4052	0,855
Viscosity at 40°C	cSt	ASTM D 445	22,4
Viscosity at 100°C	cSt	ASTM D 445	4,5
Viscosityindex (VI)		ASTM D 2270	111
Flash point (COC)	°C	ASTM D 92	210
Pourpoint	°C	ASTM D 6892	-30

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.