

EUROLUB Kühlerschutz ANF

Description/Applications:	<p>Kühlerschutz ANF is a nitrite, amine and phosphate free antifreeze based on ethylene glycol (MEG=mono ethylene ethanediol). Suitable for summer and winter with rust and frost protection. It is distinguished by its special corrosion protection additives for gray cast iron or aluminum motors suitable not foam and behaves neutrally to metals, rubber parts and seals.</p> <p>Kühlerschutz ANF must be diluted with water before use. It is hard water compatible and can be mixed with tap water(*) before filling into the cooling system to give solutions in the concentration range of 30 to 50 % by volume.</p> <p>(*)= For preparation of the coolant use clean, not overly hard water. Waste water from mining, sea water, brackish water, brine, industrial waste water are all unsuitable.</p>
----------------------------------	--

Can be used with:	BS 6580
--------------------------	---------

Delivery:	Art.-Nr. 820015	12 x 1 Liter	bottle
	Art.-Nr. 820005	4 x 5 Liter	can
	Art.-Nr. 820020	20 Liter	can
	Art.-Nr. 820060	60 Liter	hobbock
	Art.-Nr. 820208	208 Liter	drum
	Art.-Nr. 820100	Container	IBC

Water mixtures:		
(Do not mix below -20 ° C, since less than 33% Antifreeze no corrosion protection is guaranteed.)		
Ratio antifreeze	Ratio water	Frost protection to:
1 part	2 parts	-20°C
1 part	1,5 parts	-27°C
1 part	1 part	-37°C

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49(0)8165 / 95 91 – 0, Fax +49(0)8165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	print: 10.04.2018 , made 10.04.2018
	Referenz: sol
	Name: Kühlerschutz ANF PDS_GB
	Seite 1 von 1