

## EUROLUB CGLP ISO-VG 220

<b>Category:</b>	Slip and guiding way oil
------------------	--------------------------

<b>Product Features: application:</b>	<p>CGLP is formulated on good base oils and modern additives. Effective ingredients ensure optimum lubrication and oxidation protection. Good sliding properties and high adhesion. Anti-corrosion properties prevent rust and staining on sliding and bed tracks.</p> <p>The product is resistant to aqueous media such as drilling, cutting and grinding emulsions.</p> <ul style="list-style-type: none"> <li>• Very good stick-slip behavior</li> <li>• Good demulsibility</li> <li>• High adhesion</li> </ul>
---	--

<b>Recommendations:</b>	DIN 51 502
-------------------------	------------

<b>Delivery:</b>	Art.-Nr. 350020	20 Liter	plastic-canister
	Art.-Nr. 350060	60 Liter	hobbock
	Art.-Nr. 350208	208 Liter	Drum
	Art.-Nr. 350100	Container	800 – 3.000 Liter per destination

### Technical Data:

Data	Unit	Method	EUROLUB CGLP 220
Density at 15°C	kg/L	ASTM D 4052	0,891
Viscosity at 40°C	cSt	ASTM D 445	218
Viscosity at 100°C	cSt	ASTM D 445	19,5
Viscosityindex (VI)		ASTM D 2270	>90
Flash point (COC)	°C	ASTM D 92	>230
Pourpoint	°C	ASTM D 6892	<-18

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 <a href="http://www.eurolub.de">www.eurolub.de</a> , <a href="mailto:info@eurolub.de">info@eurolub.de</a>	print: 23.01.2018, made 23.01.2018
	Referenz: evcglp_01/18
	Name: CGLP 220 PDS_english_352xxx
	Seite 1 von 1