

## EUROLUB Gasmotorenöl HGM Plus SAE 40

<b>Description/Applications:</b>	<p>HGM Plus SAE 40 is a gas engine oil with high sulfated ash content. The good alkalinity protects against a rapid acidification of the engine oil and can therefore lead to longer oil life, to the knowledge of oil investigation.</p> <p>HGM Plus SAE 40 is designed for stationary gas engines in operation with sewage gas, landfills and biogas plants even under demanding conditions.</p> <ul style="list-style-type: none"> <li>• Good oil service life through high oxidation stability</li> <li>• Good lubrication and wear protection</li> <li>• High engine cleanliness</li> <li>• Good neutralization capacity</li> <li>• Protects against deposits</li> <li>• Protection against rust and corrosion</li> </ul>		
<b>Can be used with:</b>	<p>API SF / CC CCMC G2/D1 GE Jenbacher TA 1000 – 1109 for motors of series 2 and 3, class B und C MAN 3271-4 MTU 400 series MWM TR 0199-99-2105 (ash content from 0,5 % - 1,0 %)</p>		
<b>Delivery:</b>	Art.-Nr. 304020 Art.-Nr. 304060 Art.-Nr. 304208 Art.-Nr. 304100	20 Liter 60 Liter 208 Liter Container	plastic canister hobbock drum 800 – 3.000 Liter per destination

## Technical Data:

Data	Unit	Method	EUROLUB Gasmotorenöl HGM Plus SAE 40
Density at 15°C	kg/L	D 1298	0,893
Viscosity at 40°C	mm <sup>2</sup> /s	D 445	147,6
Viscosity at 100°C	mm <sup>2</sup> /s	D 445	14,7
Pourpoint	°C	D 97	-27
base number (TBN)	mgKOH/g	D 2896	9,5
Sulfate ash content	%	D 874	0,89

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.