

EUROLUB GEAR AXLE SB 75W/90

Description/Applications:	Light-gear oil for extended drain intervals according to manufacturer's specifications. Can also be used for very high mechanical and thermal stress. Observe manufacturer instructions.
----------------------------------	--

Can be used with:	API GL-3/GL-4/GL-5/MT-1 MIL-L-2105D/MIL-PRF-2105E, SAE J2360 DAF Iveco Mack GO-J MAN 341 Typ Z2/342 Typ M3 MB 235.8 Scania STO 1:0 Volvo 97312 ZF TE-ML 02B/05A/07A/12L/12N/16B/16F/17B/19C/21A
--------------------------	--

Delivery:	Art.-Nr. 347020	20 Liter	plastic canister
	Art.-Nr. 347060	60 Liter	hobbock
	Art.-Nr. 347208	208 Liter	drum
	Art.-Nr. 347100	1.000 Liter	container

Technical Data:

Data	Unit	Method	EUROLUB GEAR AXLE SB 75W/90
Density at 15°C	kg/L	DIN 51 757	0,869
Viscosity at 40°C	mm ² /s	DIN 51 562	83,9
Viscosity at 100°C	mm ² /s	DIN 51 562	15,4
Viscosity index		DIN ISO 2909	195
Flash point	°C	ISO 2592	184
Pourpoint	°C	DIN ISO 3016	-45

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 D-85386 Eching - Germany Tel. 0049/8165 / 95 91 – 0, Fax 0049/8165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	print:28.11.2018, made: 28.11.2018
	reference: NSA1818, 170418
	name: GEAR AXLE SB 75W-90 PDS_english_347xxx
	page 1 of 1