

EUROLUB Gear Fluide II D

Description / Applications:	Gear Fluide II D may be used for automatic gearboxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID fluid is required.
------------------------------------	---

Can be used with:	GM Dexron II D MB 236.6 / 236.7 MAN 339 Typ Z1 / V1 Ford Mercon M2C138-CJ /-166-H Allison C-4 CAT TO-2 Voith 55.6335 (G607) ZF TE-ML 09 / 11A / 14A
--------------------------	--

Delivery:	Art.-Nr. 373001	12 x 1 Liter	bottle
	Art.-Nr. 373020	20 Liter	can
	Art.-Nr. 373060	60 Liter	hobbock
	Art.-Nr. 373208	208 Liter	drum
	Art.-Nr. 373100	1000 Liter	IBC

Technical Data:

Data	Unit	Method	EUROLUB Gear Fluide II D
Density at 15°C	kg/L	ASTM D 4052	0,866
Viscosity at 40°C	cSt	ASTM D 445	43,2
Viscosity at 100°C	cSt	ASTM D 445	8,25
Viscosityindex (VI)		ASTM D 2270	168
Flash point (COC)	°C	ASTM D 92	198
Pourpoint	°C	ASTM D 6892	-45

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.