

EUROLUB Diesel Engine Oil 15W/40

Description/Applications:	Universal engine oil for use in diesel and gasoline engines. The high additive content guarantees excellent detergent, dispersant and antiwear properties. Ideally suited as a year-oil for mixed fleet. The operating instructions of the vehicle and engine manufactures must be followed.
----------------------------------	--

Can be used with:	ACEA A3/B4 E7 API CH-4 MB 228.1 MAN 271 Volvo VDS
--------------------------	---

Delivery:	Art.-Nr. 328018	18 Liter	can
	Art.-Nr. 328020	20 Liter	can
	Art.-Nr. 328060	60 Liter	drum
	Art.-Nr. 328208	208 Liter	drum
	Art.-Nr. 328100	Container	IBC

Technical Data:			
Data	Unit	Method	EUROLUB Diesel Engine Oil 15W/40
Density at 15°C	kg/L	D 4052	0,863
Viscosity at 40°C	cSt	D 445	101
Viscosity at 100°C	cSt	D 445	14,2
Viscosityindex (VI)		D 2270	144
Flash point (COC)	°C	D 92	min. 200
Pourpoint	°C	D 6892	-33

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49(0)8165 / 95 91 - 0, Fax +49(0)8165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	Druckdatum: 01.10.2018, erstellt am 10.10.2017
	Referenz: PENTS1540, 04.2017
	Name: Diesel Engine CH-4 15W-40 PDS_GB
	Seite 1 von 1