

## EUROLUB HD 4C SAE 40

<b>Description / Application:</b>	HD 4C 40 is a purpose powerful monograde oil. The range of services covers the requirements of Diesel engines with and without turbocharging and gasoline engines with appropriate instructions. HD 4C 40 is suitable for use in commercial vehicle diesel engines of fleets, agricultural and construction aggregates.
-----------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<b>Can be used with:</b>	ACEA E2 API SG / CF MB 227.0 / 228.0 MAN 270
--------------------------	-------------------------------------------------------

<b>Delivery:</b>	Art.-Nr. 334020	20 Liter	canister
	Art.-Nr. 334060	60 Liter	hobbock
	Art.-Nr. 334208	208 Liter	drum
	Art.-Nr. 334100	Container	800 – 3.000 Liter container per destination
	Art.-Nr. 334000	Bulk	ab 3.001 Liter Bulk per destination

### Technical Data:

Data	Unit	Method	EUROLUB HD 4C SAE 40
Density at 15°C	kg/l	DIN 12 185	0,890
Viscosity at 40°C	cSt	DIN 51 562	148,8
Viscosity at 100°C	cSt	DIN 51 562	15,1
Flash point (COC)	°C	DIN ISO 2909	102
Pourpoint	°C	DIN ISO 2592	244
Density at 15°C	kg/l	DIN ISO 3016	-15

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.