

## EUROLUB Gatteröl-Haftöl Spezial 460

<b>Category:</b>	Speciala - Adhesion Oil
------------------	-------------------------

<b>Can be used with:</b>	ISO-VG 460
--------------------------	------------

<b>Application:</b>	<p>Gatteröl-Haftöl Spezial is mixed with excellent base oils and modern additives, tailored to a good formulation. Thread-pulling and adhesive lubricating oil that forms stable and pressure-resistant lubricating films. It has excellent wetting properties and good adhesion. Vertical guides and sliding surfaces can be perfectly lubricated.</p> <ul style="list-style-type: none"> <li>• Good stick-slip behavior</li> <li>• High adhesion</li> <li>• Good demulsification behavior</li> <li>• Reduced oil consumption</li> <li>• Extended lubrication intervals</li> <li>• Improved lubrication performance</li> </ul>
---------------------	---

<b>Delivery:</b>	Art.-Nr. 361020	20 Liter	plastic canister
	Art.-Nr. 361060	60 Liter	hobbock
	Art.-Nr. 361208	208 Liter	drum
	Art.-Nr. 361100	Container	800 – 3.000 Liter per destination

### Technical Data

Data	Unit	Method	EUROLUB Gatteröl-Haftöl Spezial 460
Density at 15°C	g/cm <sup>3</sup>	DIN 51 757	0,895
Viscosity at 40°C	mm <sup>2</sup> /s	DIN 51 562	455,4
Viscosity at 100°C	mm <sup>2</sup> /s	DIN 51 562	31,2
Flash point (COC)	°C	DIN ISO 2592	240
Pourpoint	°C	DIN ISO 3016	-9

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 <a href="http://www.eurolub.de">www.eurolub.de</a> , <a href="mailto:info@eurolub.de">info@eurolub.de</a>	print: 12.12.2018, made 12.12.2018
	Referenz: ortra460/1218
	Name: Gatteröl-Haftöl 460 PDS_english_361xxx
	Seite 1 von 1