

PRODUCT INFORMATION



EUROLUB HD 4C 50

Description/Applications:	HD 4C 50 is a purpose powerful monograde oil. The range of services covers the requirements of Diesel engines with and without turbocharging and gasoline engines with appropriate instructions. HD 4C 50 is suitable for use in commercial vehicle diesel engines of fleets, agricultural and construction aggregates.
----------------------------------	---

Can be used with:	API SF/CD
--------------------------	-----------

Delivery:	Art.-Nr. 33502020 Liter canister Art.-Nr. 33506060 Liter hobbock Art.-Nr. 335208208 Liter drum Art.-Nr. 335100 Container 800 – 3.000 Liter per destination
------------------	--

Technical Data:

Data	Unit	Method	EUROLUB HD 4C 50
Density at 15°C	Kg/l	DIN EN ISO 12185	0,892
Viscosity at 40°C	mm ² /s	DIN 51 562-1	183,00
Viscosity at 100°C	mm ² /s	DIN 51 562-1	17,50
Flash point (COC)	°C	DIN ISO 2592	>220
Pourpoint	°C	DIN ISO 3016	-15

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 - 0, Fax 08165 / 95 91 - 20 www.eurolub.de , info@eurolub.de	Druckdatum: 19.10.2015, erstellt am 05.02.2014/hb
	Referenz: pusnyd, Juli 2011
	Name: HD 4C 50 PDS_GB.docxDS(GB)
	Seite 1 von 1