

EUROLUB Lagerfit GRA

Lagerfit GRA is a lithium saponified EP lubricating grease on mineral oil base with graphite.

Application:	Lagerfit GRA is suitable for lubrication of roller and friction bearings under normal and increased bearing temperatures.
Properties:	<ul style="list-style-type: none"> • oxidation stability • worked stability • water resistance • good corrosion protection • emergency operation properties • good adhesiveness

Designation DIN 51502:	KF 2 K-30
-------------------------------	-----------

Delivery:	Art.-Nr. 706400	24 x 400 g	cartridges
	Art.-Nr. 706005	5 kg	plastik hobbock
	Art.-Nr. 706015	15 kg	plastik hobbock
	Art.-Nr. 706025	25 kg	plastik hobbock
	Art.-Nr. 706180	180 kg	sheet metal drum

Technical Data:			
Data:	Unit:	Method:	EUROLUB Lagerfit GRA
Service temperature	°C		-30 to +120
Short-time admissible temperature peak value	°C		+130
Drop point	°C	ASTM D 2265	Approx.. 180 °C
Worked penetration	1/10 mm	ASTM D 217	265 to 295
Water resistance		DIN 51807 T1	1 – 90
Corrosion protection		DIN 51802	corrosion degree 0
Copper strip test		DIN 51811	1 – 100
Soap base			Li-12-hydroxystearate

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	print:07.06.2017, made 07.06.2017
	Referenz: mggr7005_01/17
	Name: Lagerfit GRA PDS_english_706xxx
	Seite 1 von 1