

EUROLUB Kühlerschutz D-40 super

Kühlerschutz D-40 Super is a nitrite-, amine-, phosphate- and borate-free radiator protection based on ethylene glycol (ethanediol, monoethylene glycol). Contains an inhibitor package based on silicate and salts of organic acids (Si-OAT).

Kühlerschutz D-40 Super must be diluted with water before use.

Description/Applications:	<p>Kühlerschutz D-40 Super provides excellent protection against frost, rust and overheating for all modern engines, especially high-load aluminum engines.</p> <p>It effectively prevents corrosion and deposits in the cooling system with its important components such as cooling ducts in the cylinder head, engine block, radiator and water pump.</p> <p>Because the special benefits of using the D-40 Super Radiator Guard are limited to the use of the D-40 Super Radiator Guard alone, it is not recommended that it be mixed with other radiator protectors.</p> <p>Radiator guard D-40 Super should be mixed with water before filling into the cooling circuit (Use clean, not too hard water to condition the coolant) and use at a concentration of 35 to 55 vol%.</p>
----------------------------------	---

Can be used with:	<p>VW TL 774 Ausf. G (Audi, Bentley, Lamborghini, Seat, Skoda, VW ab Baujahr 2008) MB 325.5 MB 325.6 MAN 324 Typ Si-OAT MTU 5048 ASTM D 3306 ASTM D 4985 SAE J 1034</p>
--------------------------	---

Delivery:	<table> <tr> <td>Art.-Nr. 834015</td> <td>12 x 1 Liter</td> <td>bottle</td> </tr> <tr> <td>Art.-Nr. 834005</td> <td>4 x 5 Liter</td> <td>can</td> </tr> <tr> <td>Art.-Nr. 834020</td> <td>20 Liter</td> <td>can</td> </tr> <tr> <td>Art.-Nr. 834060</td> <td>60 Liter</td> <td>hobbock</td> </tr> <tr> <td>Art.-Nr. 834208</td> <td>208 Liter</td> <td>drum</td> </tr> <tr> <td>Art.-Nr. 834100</td> <td>Container</td> <td>IBC</td> </tr> </table>	Art.-Nr. 834015	12 x 1 Liter	bottle	Art.-Nr. 834005	4 x 5 Liter	can	Art.-Nr. 834020	20 Liter	can	Art.-Nr. 834060	60 Liter	hobbock	Art.-Nr. 834208	208 Liter	drum	Art.-Nr. 834100	Container	IBC
Art.-Nr. 834015	12 x 1 Liter	bottle																	
Art.-Nr. 834005	4 x 5 Liter	can																	
Art.-Nr. 834020	20 Liter	can																	
Art.-Nr. 834060	60 Liter	hobbock																	
Art.-Nr. 834208	208 Liter	drum																	
Art.-Nr. 834100	Container	IBC																	

Water mixtures:

(Do not mix below -20 ° C, since less than 33% Antifreeze no corrosion protection is guaranteed.)

Ratio antifreeze	Ratio water	Frost protection to:
1 part	2 parts	-20°C
1 part	1,5 parts	-27°C
1 part	1 part	-37°C

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.