

EUROLUB Motor 1 0W/40



Description/Applications:	This motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below. Motor 1 0W/40 is suitable for long intervals between oil changes and heavy-duty engine requirements. The operating instructions of the vehicle and engine manufactures must be followed.
----------------------------------	---

Can be used with:	ACEA A3/B4 API SN MB 229.5 / 229.3 BMW Longlife-01 Ford WSS-M2C937-A VW 502.00 / 505.00 Porsche A40 Renault RN0700 / RN0710
--------------------------	--

Delivery:	Art.-Nr. 241001	12 x 1 Liter	bottle
	Art.-Nr. 241005	4 x 5 Liter	can
	Art.-Nr. 241020	20 Liter	can
	Art.-Nr. 241060	60 Liter	hobbock
	Art.-Nr. 241208	208 Liter	drum
	Art.-Nr. 241100	Container	IBC

Technical Data:

Data	Unit	Method	EUROLUB Motor 1 0W/40
Density at 15°C	kg/L	D 4052	0,845
Viscosity at 40°C	cSt	D 445	76,9
Viscosity at 100°C	cSt	D 445	13,5
Viscosityindex (VI)		D 2270	180
Flash point (COC)	°C	D 92	226
Pourpoint	°C	D 6892	-54

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.