

## EUROLUB Formel 1 SAE 5W/40

<b>Description / Applications:</b>	Formel 1 SAE 5W/40 is a high-performance engine oil produced using HC synthetic oils with a wide area of application. Its high level of performance is achieved through the interaction of selected base oils and advanced additives. The operating instructions of the vehicle and engine manufactures must be followed.		
<b>Can be used with:</b>	ACEA A3 / B4 API SN / CF MB 229.3 / 226.5 BMW Longlife-01 VW 502.00 / 505.00 GM-LL-B-025 Renault 0700 / 0710 PSA B71 2296 Porsche A40		
<b>Delivery:</b>	Art.-Nr. 216001	12 x 1 Liter	bottle
	Art.-Nr. 216005	4 x 5 Liter	can
	Art.-Nr. 216020	20 Liter	can
	Art.-Nr. 216060	60 Liter	hobbock
	Art.-Nr. 216208	208 Liter	drum
	Art.-Nr. 216100	Container	IBC

### Technical Data:

Data	Unit	Method	EUROLUB Formel 1 SAE 5W/40
Density at 15°C	kg/L	ASTM D 7042	0,852
Viscosity at 40°C	cSt	ASTM D 7042	86,0
Viscosity at 100°C	cSt	ASTM D 7042	14,3
Viscosityindex (VI)		ASTM D 7042	171
Flash point (COC)	°C	DIN EN ISO 2592	236
Pourpoint	°C	DIN EN ISO 3016	-33

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49(0)8165 / 95 91 - 0, Fax +49(0)8165 / 95 91 - 20 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	print: 20.11.2018, made 20.11.2018
	Referenz: R20068, 20.02.2017
	Name: Formel 1 SAE 5W-40 PDS_english_216xxx
	Seite 1 von 1