

EUROLUB Multitec SAE 10W/40

Description / Applications:	Multitec 10W/40 is the ideal oil for the mixed fleet of vehicles, as a universal low-viscosity engine oil. can be found in freight forwarders, municipalities and in the construction industry. A uniform engine oil for all vehicles eliminates confusion and makes stock keeping more economical. Because of its very high diesel performance, the Multitec 10W/40 can be used in all commercial and construction vehicles, including those with turbocharging, as well as in gasoline engines and diesel car engines with and without turbocharging. This oil is suitable for use in Euro 4 and Euro 5 engines. Manufacturer's instructions are to be considered !!
------------------------------------	---

Can be used with:	ACEA A3 / B4, E7 MB 228.3 MAN M 3275 Renault VI RLD-2 Cummins CES 20077 / 20078 Mack EO-N Global DHD-1 Deutz DQC III-10 JASO DH-1	API CI-4 / SL Volvo VDS-3 MTU Type 2 Cat ECF-2 / ECF-1-a Detroit Diesel 93K215
--------------------------	---	--

Delivery:	Art.-Nr. 317005	4 x 5 Liter	can
	Art.-Nr. 317020	20 Liter	can
	Art.-Nr. 317060	60 Liter	hobbock
	Art.-Nr. 317208	208 Liter	drum
	Art.-Nr. 317100	Container	IBC

Technical Data:

Data	Unit	Method	EUROLUB Multitec SAE 10W/40
Density at 15°C	kg/L	D 4052	0,863
Viscosity at 40°C	cSt	D 445	85,8
Viscosity at 100°C	cSt	D 445	13,8
Viscosityindex (VI)		D 2270	156
Flash point (COC)	°C	D 92	222
Pourpoint	°C	D 6892	-36

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49(0)8165 / 95 91 - 0, Fax +49(0)8165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	print: 15.04.2019, made 15.04.2019
	Referenz: NSA1015, 30.03.2018
	Name: Multitec SAE 10W-40 PDS_english_317xxx
	Seite 1 von 1