

EUROLUB Lowcargo SAE 5W/30

Description / Applications:	This lubricant has mainly been developed for heavy diesel engines even under the toughest operation conditions and all over the year round. This product is very suitable for Euro 5 and Euro 6 engines in combination with diesel fuel with a low Sulphur content. This engine oil is also suitable for application in engines with or without particle filters and exhaust catalysts. This motoroil is one of the group "low SAPS" lubricants.		
Can be used with:	ACEA E6, E7, E9 API CK-4 / SN MB 228.51 / 228.31 MAN M 3777 / M 3677 / M 3477 / M 3271-1 Volvo VDS-4.5 Scania Low Ash / LDF-4 Mack EO-S 4.5 Renault RLD-4 MTU Type 3.1 / JASO DH-2 / Voith Class B Cummins CES 20086 / CAT ECF-3 Deutz DQC IV-10 LA Detroit Diesel DDC 93K222		
Delivery:	Art.-Nr. 232005	4 x 5 Liter	can
	Art.-Nr. 232020	20 liter	plastic can
	Art.-Nr. 232060	60 liter	hobbock
	Art.-Nr. 232208	208 liter	drum
	Art.-Nr. 232100	Container	IBC

Technical Data:

Data	Unit	Method	EUROLUB Lowcargo SAE 5W/30
Density at 15°C	kg/L	D 4052	0,855
Viscosity at 40°C	cSt	D 445	65,0
Viscosity at 100°C	cSt	D 445	11,3
Viscosityindex (VI)		D 2270	>159
Flash point (COC)	°C	D 92	>200
Pourpoint	°C	D 6892	-39

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49(0)8165 / 95 91 - 0, Fax +49(0)8165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	print: 29.01.2019, made 29.01.2019
	Referenz: P17989, 07/2018
	Name: Lowcargo SAE 5W-30 PDS_english_232xxx
	Seite 1 von 1