

EUROLUB HLP AF ISO-VG 32

Category: HLP Hydraulic Fluids

**Product Features:
application:** The HLP hydraulic oils is based on paraffinic base oil and modern additive technology. Effective zinc and ash free components guarantee optimal lubrication and long term protection against oxidation. During the process fine filtration is possible without the risk of losing valuable ingredients. Because of the high viscosity index the lubricating effect of the oil remains unaffected even at very high temperatures.

Recommendations:	DIN 51 524 / part 2	FZG-Test A8, 3/90 load stage: 13
	DIN 51 517 (HLP 46)	AIST 127 + 136
	ISO 11158	DBL 6713.10
	SIS SS 155434	

Delivery: Art.-Nr. 522100 Container 800 – 3.000 Liter per destination

Technical Data:			
Data	Unit	Method	EUROLUB HLP AF 32
Density at 15°C	kg/L	DIN EN ISO 12185	0,858
Viscosity at 40°C	cSt	DIN 51562-1	31,4
Viscosity at 100°C	cSt	DIN 51562-1	5,6
Viscosityindex (VI)		DIN ISO 2909	114
Flash point (COC)	°C	DIN ISO 2592	230
Pourpoint	°C	DIN ISO 3016	-27

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 www.eurolub.de , info@eurolub.de	print, 28.11.2018, made 28.11.2018
	Referenz: pen12/17
	Name: HLP AF 32 PDS_english_522xxx
	Seite 1 von 1