

## EUROLUB GEAR EP 80W

<b>Description/Applications:</b>	It contains high quality, carefully refined base oils, blended with a balanced combination of additives. This guarantees a high load-bearing capacity, wear protection and high oxidation stability. Above average viscosity-temperature behaviour, a low pour point and - last but not least –suppression of the tendency to form foam make it possible to use it under a variety of operating conditions.
----------------------------------	---

<b>Can be used with:</b>	API GL-4 MAN 341 M1 MB 235.1 ZF TE-ML 02
--------------------------	---

<b>Delivery:</b>	Art.-Nr. 342020	20 Liter	canister
	Art.-Nr. 342060	60 Liter	hobbock
	Art.-Nr. 342208	208 Liter	drum
	Art.-Nr. 342100	Container	IBC 1.000L

<b>Technical Data:</b>			
<b>Data</b>	<b>Unit</b>	<b>Method</b>	<b>EUROLUB Gear EP 80W</b>
Density at 15°C	kg/L	ASTM D 4052	0,882
Viscosity at 40°C	cSt	ASTM D 445	78
Viscosity at 100°C	cSt	ASTM D 445	9,5
Viscosityindex (VI)		ASTM D 2270	>90
Flash point (COC)	°C	ASTM D 92	>210
Pourpoint	°C	ASTM D 6892	<-27

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. 08165 / 95 91 – 0, Fax 08165 / 95 91 - 20 <a href="http://www.eurolub.com">www.eurolub.com</a> , <a href="mailto:info@eurolub.com">info@eurolub.com</a>	Druckdatum: 27.09.2017, erstellt am 27.09.2017
	Referenz: EVHYGA80, 040917
	Name: GEAR EP 80W PDS_english_342xxx
	Seite 1 von 1