



## SAFETY DATA SHEET

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

*Product name:* LITHI-TEK 4500  
*Manufacturer:* KRETETEK INDUSTRIES  
66 RIVER ROAD  
HUDSON, NH 03051  
*Telephone:* 855-573-8383  
*In case of emergency call:* 800-424-9300  
CHEMTREC

### 2. HAZARDS IDENTIFICATION

GHS Classification: Skin Irrit. 2  
Eye Irrit. 2

Hazards summary: Alkaline. Irritation to eyes and skin. May cause irritation to the respiratory system. Caution – spillages may be slippery.

Hazard pictogram:



Signal word: Warning

Hazard statements:

H315: Causes skin irritation  
H 319: Causes serious eye irritation.

Precautionary statements:

P262: Do not get in eyes, on skin, or on clothing.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical and Common Name	CAS Number
Water	7732-18-5
Silicic acid, lithium salt; lithium silicate	12627-14-4

### 4. FIRST AID MEASURES

*Eye:* In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

*Skin:* In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention.

*Inhalation:* Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

*Ingestion:* If swallowed, DO NOT induce vomiting. Get medical attention immediately. If victim is fully conscious, give a cupful of water. Never give anything by mouth to an unconscious person.

## 5. FIRE FIGHTING MEASURES

*Flammable limits:* This material is noncombustible.  
*Extinguishing Media:* This material is compatible with all extinguishing media.  
*Hazards to fire-fighters:* See Section 3 for information on hazards when this material is present in the area of a fire.  
*Fire-fighting equipment:* The following protective equipment for fire fighters is recommended when this material is present in the area of a fire: chemical goggles, body-covering protective clothing, chemical resistant gloves, and rubber boots.

## 6. ACCIDENTAL RELEASE MEASURES

*Personal protection:* Wear chemical goggles, body-covering protective clothing, chemical resistant gloves, and rubber boots. See section 8.  
*Environmental Hazards:* Sinks and mixes with water. High pH of this material is harmful to aquatic life, see Section 12. Only water will evaporate from a spill of this material.  
*Small spill cleanup:* Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).  
*Large spill cleanup:* Keep unnecessary people away; isolate hazard area and deny entry. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent runoff from entering into storm sewers and ditches which lead to natural waterways. Isolate, dike and store discharged material, if possible. Use sand or earth to contain spilled material.  
*CERCLA RQ:* There is no CERCLA Reportable Quantity for this material. If a spill goes off site, notification of state and local authorities is recommended.

## 7. HANDLING AND STORAGE

*Handling:* Avoid contact with eyes, skin and clothing. Avoid breathing spray mist. Keep container closed. Promptly clean residue from closures with cloth dampened with water. Promptly clean up spills.  
*Storage:* Keep containers closed. Store in clean plastic containers. Separate from acids, reactive metals, and ammonium salts. Keep from freezing. Recommended storage temperature 15°-60° C (59°-140° F). Do not store in aluminum, steel, fiberglass, copper, brass, zinc or galvanized containers.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<i>Engineering controls:</i>	Use with adequate ventilation. Keep containers closed. Safety shower and eyewash fountain should be within direct access.
<i>Respiratory protection:</i>	Use a NIOSH-approved dust and mist respirator where spray mist occurs. Observe OSHA regulations for respirator use (29 C.F.R. § 1910.134)
<i>Skin protection:</i>	Wear body-covering protective clothing and gloves.
<i>Eye protection:</i>	Wear chemical goggles.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<i>Appearance:</i>	Liquid.
<i>Color:</i>	Clear to opalescent white.
<i>Odor:</i>	Odorless or musty odor.
<i>pH:</i>	Approximately 10.8
<i>Density:</i>	1.2 g/cm <sup>3</sup> (20°C); 25° Bé; 10.0 lbs/gal
<i>Solubility in water:</i>	Miscible.

## 10. STABILITY AND REACTIVITY

<i>Stability:</i>	This material is stable under all conditions of use and storage.
<i>Conditions to avoid:</i>	None.
<i>Materials to avoid:</i>	Gels and generates heat when mixed with acid. Absorbs carbon dioxide on exposure to air. May react with ammonium salts resulting in evolution of ammonia gas. Flammable hydrogen gas may be produced on contact with aluminum, tin, lead, and zinc.
<i>Hazardous decomposition products:</i>	Hydrogen.

## 11. TOXICOLOGICAL INFORMATION

<i>Acute Data:</i>	When tested for primary irritation potential, a similar material caused moderate irritation to the eyes and moderate irritation to the skin.
<i>Subchronic Data:</i>	Repeated ingestion or ingestion of large doses of soluble lithium compounds is reported to cause temporary mental function impairment.
<i>Special Studies:</i>	Repeated ingestion or ingestion of large doses of soluble lithium compounds during pregnancy is reported to cause fetal abnormalities. Frequent ingestion over extended periods of time of gram quantities of silicates is associated with the formation kidney stones and other siliceous urinary calculi in humans. Lithium silicate is not listed by IARC, NTP or OSHA as a carcinogen.

## 12. ECOLOGICAL INFORMATION

<i>Eco toxicity:</i>	This product has not been tested for ecotoxicity potential.
<i>Environmental Fate:</i>	The high pH of this material may be acutely harmful to aquatic life. It does not contribute to BOD.
<i>Physical/Chemical:</i>	Sinks and mixes with water. Only water will evaporate from this material.

## 13. DISPOSAL CONSIDERATIONS

<i>Classification:</i>	Disposed material is not a hazardous waste.
<i>Disposal Method:</i>	Dispose in accordance with federal, state and local regulations and permits.

## 14. TRANSPORT INFORMATION

<i>DOT UN Status:</i>	This material is not regulated hazardous material for transportation.
-----------------------	-----------------------------------------------------------------------

## 15. REGULATORY INFORMATION

<i>CERCLA:</i>	No CERCLA Reportable Quantity has been established for this material.
<i>SARA TITLE III:</i>	Not an Extremely Hazardous Substance under § 302. Not a Toxic Chemical under § 313. Hazard Categories under § § 311/312: Acute
<i>TSCA:</i>	All ingredients of this material are listed on the TSCA inventory.

## 16. OTHER INFORMATION

Disclaimer: the information contained herein is based on the data available and is believed to be accurate, however, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.