





LIGHTBARS





27 SERIES **SAE Class I LED Lightbar**

ECCO 27 Series Lightbars are versatile and powerful warning devices suitable for a range of vehicle types and duties. There are numerous options and lengths available and the lightbars can either be mounted permanently to the vehicle or mounted using an optional roof mounting kit. The 27 Series is suitable for many vehicle applications and features reflective LED modules, a durable aluminum chassis and polycarbonate lenses. Available in seven standard configurations, the 27 Series can be configured with either centrally controlled or independent flashing warning modules, offering a choice of either 3, 8, 12 or 22 LEDs per module, including dual color options. Stop-Tail-Indicator, worklamp/takedown and alley light modules are also available as well as an integrated Safety Director to control the rear warning modules independently.

Features

- Medium-profile chassis
- Three, eight, 12 and 22 Reflective LED modules
- Integrated LED Safety Director™
- 19 flash patterns (independent flashing)
- 31 flash patterns (centrally controlled)
- Aluminum chassis, polycarbonate base and lens
- Magnet mount available for 22" lightbars (EZ2122MG)
- · Range of strap mounting accessory kits
- Four color options Amber, Blue, Red, and Clear
- Nine length options 22", 36", 44", 47", 52", 58", 69", 80" and 91"
- Seven standard chassis configurations
- Customizable configuration available
- Height: 2.7", width: 12.2"
- Temperature Range: -22°F to +122°F (-30°C to +50°C)

Symbols / Features Guide

Independent Flashing (IF) indicates the lightbars modules have individual electronic circuits that control their operation. Centrally Controlled (CC) modules are operated via a centrally mounted control board.

Warning Modules - Independent Flashing



Warning Modules - Centrally Controlled



Auxiliary Modules

STT LED Stop-Tail-Turn

W **LED Worklamps**

A **LED Alley Lights**

REF Integrated LED Safety Director

T 800-635-5900 | orders@eccogroup.com

27 SERIES - LED Lightbar Standard Configurations

WARNING LIGHTING | DIRECTIONAL LIGHTING | LIGHTBARS | WHITE LIGHTING | REVERSING SAFETY

22" / 0.55m	#	V	Α	LEDs	WL	AL	STT	Module Safety Director	(b)
FRONT IF	27-00001-E	12	2.0	4	-	-	-	-	5 years
FRONT IF BACK REFB	27-00002-E	12	3.0	6	-	-	-	-	5 years
REFB REFB BACK REFB REFB	27-00003-E	12	4.0	8	-	-	-	-	5 years
47" / 1.19m	#	٧	А	LEDs	WL	AL	STT	Module Safety Director	(
REFS REFS REFS REFS REFS REFS REFS	27-00004-E	12	7.0	14	-	-	-	-	5 years
52" / 1.32m	#	٧	А	LEDs	WL	AL	STT	Module Safety Director	(L)
ROOT CC	27-00006-E	12	8.0	16	-	-	-	10	5 years
THE REFE DATE DATE DATE DATE DATE DATE DATE DAT	27-00009-E	12	12.0	16	-	-	-	6	5 years
58" / 1.69m	#	٧	А	LEDs	WL	AL	STT	Module Safety Director	(
CC BOO REE BOO REE BOO REE	27-00007-E	12	8.0	10	2	-	2	-	5 years

T 800-635-5900 | orders@eccogroup.com