

Product Name:	Bluelab Soil pH Meter
Product Code:	METSOILPH
UPC Code:	9421024920098
Country of Origin:	New Zealand
Tariff Code:	9027.80
Shipping Quantity:	Sold as singular unit
Packaging Information:	
Packaged Weight:	0.39 kg / 0.86 lb
Packaged Length:	180 mm / 7.086 in
Packaged Width:	110 mm / 4.33 in
Packaged Height:	83 mm / 3.267 in

Sales Description:

NOTE: this copy can be used in brochures, catalogues or online

The portable way to measure pH of growing media

Direct soil pH measuring made simple.

Reliably measure the pH level of media including soil, coco and rockwool, with the Bluelab® Soil pH Meter.

Using the dibber ensures media is free from coarse particles, the soil pH probe fits the hole for a direct pH measurement. This meter can also measure soil solutions/slurries.

The Bluelab® Soil pH Meter can be used by everybody from the home enthusiast through to more robust commercial applications. Team with Bluelab solutions and the convenient Bluelab® Carry Case.

Probe cable length: 2 meters / 6.5 feet

Features:

- Replaceable, toughened single junction soil pH probe included
- Lightweight and portable
- Large easy to read display
- Simple push button pH calibration
- Simple two point calibration process with 30 day calibration indicator
- Backlit LCD display
- Over range and under range indicators
- 2x AAA alkaline batteries included
- Low battery indicator
- Auto off function

Product Guarantee:

Five year free repair or replacement guarantee*.

* Six months for Soil pH Probe.



Product Image:



Product images available for Screen or Web use:

- Bluelab-SoilpHMeter-MR-flat-RGB.jpg
- Bluelab-SoilpHMeter-WEB.jpg
- Bluelab-SoilpHMeter-WEB-Sml.jpg

Product images available for PRINT:

Note: these images are high resolution in CMYK.

- Bluelab-SoilpHMeter-MR-flat-CMYK.tif

Technical Specifications:

Measurement Range:	0.0 – 14.0 pH
Resolution:	0.1 pH 1 °C / 1 °F
Accuracy at 25°C / 77°F:	± 0.1 pH
Automatic Temperature Compensation:	No
Operating Environment:	0 – 50 °C / 32 – 122 °F
Calibration:	Two point, pH 7.0 & pH 4.0 or pH 10.0
Power Source:	2 x AAA alkaline batteries
User Manual Languages Available:	English; Nederlands
Certifications:	CE and FCC

{This Product Information Sheet is NOT intended for distribution to end users.}