

#### NOTES:

1. DIMENSIONS IN INCHES [MILLIMETERS (FOR REFERENCE)]

#### PROPRIETARY AND CONFIDENTIAL INFORMATION


THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATES ("CODE3") AND IS ISSUED IN CONFIDENCE TO RECIPIENT FOR ENGINEERING INFORMATION PURPOSES ONLY. THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN MAY NOT BE USED, COPIED, REPRODUCED OR OTHERWISE DISCLOSED IN PART OR IN WHOLE TO THIRD PARTIES OR USED FOR ANY OTHER PURPOSE WITHOUT PRIOR CODE3 WRITTEN CONSENT. CODE3 RESERVES ALL PATENT, COPYRIGHT, TRADE SECRET AND OTHER PROPRIETARY RIGHTS IN THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN. REPRODUCTION, REPRODUCTION IN WHOLE OR IN PART, AND SALES RIGHTS THERETO, THIS DRAWING IS SUBJECT TO RECALL BY CODE3 AT ANY TIME, AND YOUR POSSESSION AND/OR USE CONSTITUTES ACCEPTANCE OF THESE TERMS. ©2024 ELECTRONIC CONTROLS COMPANY

REVISION HISTORY		
REV.	DESCRIPTION	DATE
07	REVISED PER EB0010	2024-12-04
A	INITIAL RELEASE PER EB0010	2024-12-10
B	REVISED PER ES0064	2026-01-09

## SPECIFICATIONS

1. CERTIFICATIONS: SAE J595 (AUG 2021) CLASS 1M; IP6KX/IPX7/IPX9K; REG10; REG65; CE; UKCA; CTICK; CA13; ROHS;  
Note: Unique components, accessories, and hardware kits are not typically included in the Product Certification Test Protocols. Unless otherwise specified, the Product Certifications referred to herein are predicated upon the base product model configuration.
2. FLASH MODE:  
SINGLE:  $75 \pm 5$  FLASHES PER MINUTE  
SINGLE:  $375 \pm 5$  FLASHES PER MINUTE  
DOUBLE:  $75 \pm 5$  FLASHES PER MINUTE
3. VOLTAGE (NOMINAL): 12 - 24 VDC
4. VOLTAGE (EXTREME): 9 - 32 VDC
5. CURRENT (PEAK): SEE CHART (@ 12 VDC NOMINAL)
6. POWER (MAXIMUM): SEE CHART (@ 12 VDC NOMINAL)
7. TEMPERATURE RANGE: -40°C (-40°F) to 65°C (149°F)
8. CONNECTION: 5-22 AWG WIRES
9. MOUNTING: 2 Bolt
10. BASE MATERIAL: Aluminum
11. LENS MATERIAL: Polycarbonate
12. PRODUCT WEIGHT: 0.05LBS (0.02Kg)

FGS. PRODUCT CHART			
FGS. NO.	COLOR	CURRENT (PEAK) A	POWER (MAX) W
CD3602RW	RED/WHT	0.43	5.50
CD3602BW	BLU/WHT	0.43	5.50
CD3602RB	RED/BLU	0.43	5.50
CD3602AW	AMB/WHT	0.41	5.25

SCALE 1:1			APPROVALS	DATE	 <b>DIR,SURF,THIN,6LED,12-24V</b> Americas (314) 426-2700   Europe +44 (0)113 239 1111   Asia Pacific +61 (0)7 32937900 SEE CHART
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE.			DRAWN BY MDH	2026-01-07	
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:			CHECKED BTK	2026-01-09	
MILLIMETERS DECIMALS      INCHES DECIMALS      ANGLES XX. ± 1.0mm      XX. ± 0.1      ± 0.5° XXX. ± 0.5mm      XXX. ± 0.04      FRACTIONS X.XXX ± 0.02      ± 1/64			MECH. ENG. HA	2026-01-08	
ELEC. ENG. BWR			TEST ENG. JRT	2026-01-07	
SALES.					
			SIZE: A	DWG. NO. CD3602XX	REV. B
Electronically Controlled Use Latest Copy			SHEET 1 OF 1	Project: EB0010	Date Created: 2024-08-29