

21TR[™] PLUS/21IF[™] - 21 SERIES Delivers Off-Angle Performance

The 21TR[™] Plus and 21IF are a superior directional and deliver off-angle performance. This lightbar is economical, yet advanced, and offers standard features providing the brightest basic lightbar on the market. The 21TR[™] Plus features deluxe central controller, 40+ flash patterns, NarrowStik[™], flashing takedown and alleys, cruise lights, and a multi-color feature is available. The 21IF is an independent flashing LED lightbar that features flashing takedown and alleys, independently flashing lightheads, and user selectable flash patterns. Each lighthead has a clear lens, LED takedowns and alleys, and a dimming mode.

Features

21TR PLUS

- Central controller (CC)
- ArrowStik[™]
- Flashing takedown and alleys
- Cruise lights (flicker and safety)
- Dual-color feature available
- SmartPro $^{\scriptscriptstyle \rm T\!M}$ controller allows one touch setting/changing of flash patterns

21IF

- Each lighthead is independent flashing (IF)
- Flashing takedowns and alleys available with optional 940 flasher
- User selectable flash patters available for each lighthead

Options

- Length options 18", 22", 36", 44", 47", 52", 58", 69", 80", & 91"
- Stop/turn/tail lights
- 795H Opticom[™] or N-3 Emitter
- Upper lenses available in red, blue, amber, tinted or black top lenses
- Quick disconnect
- Lower lens available in amber, clear or tinted for specific configurations

Adjustable Mounting Kits

MODEL	WEIGHT	VERTICAL ADJUSTMENT
ADMKIT	2.9 lbs	0.625"

• Universal, low-rise fit that allows a lightbar to be adjusted to perfectly match the contours of today's emergency vehicles

• The adjustable mounting feet are pursuit speed tested (extra brackets are not required to meet pursuit speed rating)

• The bracket system allows the lightbar to be adjusted for height and front/back angle to ensure the lightbar is perfectly level









21TR[™] PLUS/21IF[™] - 21 SERIES Standard Configurations

CUSTOM CONFIGURATIONS AVAILABLE ON C3VUE

12V 40+ FP

2.1" H x 12.3" D

MODEL	LENGTH	CHASSIS DIAGRAM
21-31116-C	22″	
21-31081-C	44″	Passenger's Side
21-31082-C	47″	Driver's Side
21-31084-C	47″	Passenger's Side
21-31085-C	47″	Driver's Side

Call Code3 For Additional Configurations

Models above include: 15' (4.6m) cable with driver side exit and adjustable mounting feet, excluding 21-31116-C which includes permanent mounting kit

