

PRIZM™II PERIMETER LIGHTS

DIRECTIONAL WARNING FOR ANY FIRE OR EMS APPARATUS



REPLACE " " with A = Amber, B = Blue, G = Green, R = Red, W = White

WITH BEZEL	WITHOUT BEZEL	TYPE	LENS	ILLUMINATION COLORS
468_BZ-75	468_-75	Single, 8 LED	*	A, B, G, R, W
468C_BZ-75	468C_-75	Single, 8 LED	C	A, B, G, R
4612_BZ-75	4612_-75	Single, 12 LED	*	A, B, G, R, W
4612C_BZ-75	4612C_-75	Single, 12 LED	C	A, B, G, R
4612C__BZ-75	4612C__-75	Split, 12 LED	C	AW, RA, RB, RW
4612SCWBZ	-	Steady Burn, 12 LED	C	W
4622C__BZ	4622C__	Dual, 22 LED	C	AW, BA, BW, RA, RB, RW
378_BZ-75	378_-75	Single, 8 LED	*	A, B, R, W
378C_BZ-75	378C_-75	Single, 8 LED	C	A, B, R
378SCRBBZ	-	Steady Burn, 8 LED	C	R
3712_BZ-75	3712_-75	Single, 12 LED	*	A, B, R, W
3712C_BZ-75	3712C_-75	Single, 12 LED	C	A, B, G, R, W
3712C__BZ-75	3712C__-75	Split, 12 LED	C	AW, RA, RB, RW
3712SCABZ	-	Steady Burn, 12 LED	C	A
3722C__BZ	3722C__	Dual, 22 LED	C	AW, BA, BW, RB, RW
798_BZ-75	798_-75	Single, 8 LED	*	A, B, R, W
798C_BZ-75	798C_-75	Single, 8 LED	C	A, B, R
798SCRBBZ	-	Steady Burn, 8 LED	C	R
798S_BZ	-	Steady Burn, 8 LED	*	A, R
7912_BZ-75	7912_-75	Single, 12 LED	*	A, B, R, W
7912C_BZ-75	7912C_-75	Single, 12 LED	C	A, B, G, R, W
7912C__BZ-75	7912C__-75	Split, 12 LED	C	AW, RA, RB, RW
7912SCRBBZ	-	Steady Burn, 12 LED	C	RB
7922C__BZ	7922C__	Dual, 22 LED	C	AW, BA, BW, RA, RB, RW

These perimeter warning lights offer advanced dual reflector LED technology that delivers brighter and more focused output for superior visibility. The optional, multi-color and vertically-split lighthead assemblies provide maximum versatility to accommodate any application. Choose from single or a triple row of intense LEDs powered by PriZm™II technology. Features include synchronization between multiple lighthead assemblies, easy install or retrofit as well as dimming and steady burn functions. Water resistant seals included.

VOLTS	12V
DIMS	5.0" H x 9.2" L x 1.6" D 127mm H x 233mm L x 39mm D (378, 3712, 3722) (with bezel) 6.0" H x 8.4" L x 1.6" D 152mm H x 214mm L x 39mm D (468, 4612, 4622) (with bezel) 9.1" H x 11.1" L x 1.6" D 231mm H x 282mm L x 39mm D (798, 7912, 7922) (with bezel)
LEDS	468, 4612, 4622 - 1 row of LEDs 378, 3712, 3722 - 1 row of LEDs 98, 7912, 7922 - 3 rows of LEDs
FLASH PATTERNS	30
CERTS	CLASS I (SAE J595), CA T13, NFPA, KKK-A 1822F
DETAILS	<ul style="list-style-type: none"> Surface mount Low amp draw Dimming Sync-capable between multiple lighthead assemblies provides a full range of flash capabilities ever required Water resistant seals Illumination Colors dictates lens color*

PRIZM™II PERIMETER LIGHTS

DIRECTIONAL WARNING FOR ANY FIRE OR EMS APPARATUS

