



LIGHTBARS



DEFENDER® - 26 SERIES

Higher Efficiency With Less Components

The Defender® with QuadCore™ is an exciting advancement of our Defender series lightbar. The QuadCore™ lightheads utilize a streamlined design that uses less parts and a new, more efficient heat sink that allows for outstanding heat dissipation. Along with the new lightheads, a new central controller board opens up a whole new world of flash pattern options. With the new central controller board, you can synchronize individual banks of lightheads giving you the ultimate in flash pattern customizability. Features include single and multicolor models, one touch setting/changing of flash patterns, dimming feature, corner cruise lights, built-in NarrowStik™ function, and flasher/steady burn for work and scene lights

Features

- Quadcore™ lightheads utilize a more efficient heat sink that allows for outstanding heat dissipation and light output
- An 8 output central controller board allows for synchronization of individual banks of lightheads
- 3" single-color (6 LED), 6" single-color (12 LED), and dual-color (24 LED) lightheads available
- Dimming feature
- Cruise lights
- Built-in ArrowStik™ function with SmartPro™ controller allows one touch setting/changing of flash patterns

Options

- Length options - 11", 18", 23", 36", 44", 47", 52", 58", 70", 82", and 94"
- Opticom™ 795H infrared LED emitter (E795LP)
- Quick disconnect cable
- Black intermolded solar barrier is standard red, blue or amber lenses available

Adjustable Mounting Kits

MODEL	WEIGHT	VERTICAL ADJUSTMENT
ADMKIT	2.9 lbs	0.625"

- Universal, low-rise fit that allows a lightbar to be adjusted to perfectly match the contours of today's emergency vehicles
- The adjustable mounting feet are pursuit speed tested (extra brackets are not required to meet pursuit speed rating)
- The bracket system allows the lightbar to be adjusted for height and front/back angle to ensure the lightbar is perfectly level

Precisely adjust the lightbar here



DEFENDER® - 26 SERIES

Standard Configurations

CUSTOM CONFIGURATIONS AVAILABLE ON C3VUE



12V | 40+ FP
2.25" H x 13.5" D

MODEL	LENGTH	CHASSIS DIAGRAM
26-30154-C	23"	
26-30155-C	47"	
26-30157-C	52"	
26-30156-C	58"	
26-30161-C	58"	

Call Code3 For Additional Configurations

Models above include: 15' (4.6m) cable with driver side exit and adjustable mounting feet, excluding 26-30154-C which includes permanent mounting kit