



LIGHTBARS



RMX™ - 34 SERIES Two Levels Of Unmatched Light Output

The RMX lightbar is designed with two levels of warning to deliver unmatched light output and increases firefighter safety. Advanced PriZm™ II dual reflector LED technology provides a brighter signal for superior visibility and safety. A full range of configurations are available to meet all your emergency vehicle needs. Features include one touch setting/changing of flash patterns, LED dimming feature, small gauge multi-conductor cable, and a 5 year warranty.

Features

- One touch setting/changing of flash patterns (default is NFPA QuadFlash 75)
- LED dimming feature
- Small gauge multi-conductor cable provides easy installation
- Lenses available in red, blue, amber, or clear
- 12 LED and 8 LED PriZm™ II lighthoods in front and rear position

Options

- Length options - 18", 36", 47", 58", 69", 80", & 91"

ADJUSTABLE MOUNTING KITS

MODEL	WEIGHT	VERTICAL ADJUSTMENT
ADMKIT	2.9 lbs	0.625"

- Universal, low-rise fit that allows a lightbar to be adjusted to perfectly match the contours of today's emergency vehicles
- The adjustable mounting feet are pursuit speed tested (extra brackets are not required to meet pursuit speed rating)
- The bracket system allows the lightbar to be adjusted for height and front/back angle to ensure the lightbar is perfectly level

Precisely adjust the lightbar here



RMX™ - 34 SERIES

Standard Configurations



12V | 40+ FP
5.3" H x 12.3" D

MODEL	LENGTH	CHASSIS DIAGRAM
34-30046-C 34-30045-C	18" 18"	
34-30047-C	58"	
34-30048-C	69"	
34-30049-C	91"	

Call Code3 For Additional Configurations

Models above 69" and over include: 35' (10.7m) cable with driver side exit and MX kit mount.

Models above 58" and below include: 15' (4.6m) cable with driver side exit and permanent mounting kit, excluding 34-30046-C which includes passenger side exit and 34-30047-C which includes MX kit mount.