

CW3100 SERIES SINGLE ROW

DT04-2P
Female DEU
Mate: DT06-2S



Youtube.com/Code3Inc

Code 3's single row utility bars offer bright white light output with low amp draw and a relatively low profile. They are available in three lengths with multiple mounting options. These bars are an ideal choice for a variety of applications. Features include 12-24 VDC operation, deutsch connector, powerful five-watt LEDs, flood or combination flood/spot beam patterns, durable aluminum housing and a tough polycarbonate lens.

VOLTS	12-24V
DIMS	2.0" H x 9.3" L x 2.0" D 51mm H x 193mm L x 84mm D (CW3109) 2.0" H x 20.6" L x 2.0" D 51mm H x 356mm L x 84mm D (CW3114) 2.0" H x 32.0" L x 2.0" D 51mm H x 597mm L x 84mm D (CW3124)
CERTS	CE, IP67, IP69K, RoHS
DETAILS	<ul style="list-style-type: none"> ▪ Deutsch connector ▪ Built-in vent to prevent fogging ▪ High-intensity beam ▪ Adjustable end or extrusion mount ▪ Aluminum heatsink housing and polycarbonate lens ▪ Temperature range: -40°F to 158°F (-40°C to 70°C)

MODEL	TYPE	LUMENS (RAW)	AMPS
CW3109	Flood	875	0.8
CW3120	Flood / Spot Combo	2,175	1.8
CW3132	Flood / Spot Combo	3,475	3.0

