



NOTES:

1. CABLE NOT SHOWN FOR CLARITY:
3-18 AWG CONDUCTOR CABLE
BLACK- GROUND(-)
RED - FLOOD LEDS(+)
GREEN - AUXILIARY LEDS(+)
2. CABLE DIMENSION IS 19.00 ± 1.00 [483 ± 25] FROM CABLE EXIT TO END OF WIRES
3. ROHS COMPLIANT
4. DIMENSIONS IN INCHES [MILLIMETERS (FOR REFERENCE)]

PROPRIETARY AND CONFIDENTIAL INFORMATION

THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATES ("ECCO") AND IS ISSUED IN CONFIDENCE TO RECIPIENT FOR ENGINEERING INFORMATION PURPOSES ONLY. THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN MAY NOT BE USED, COPIED, REPRODUCED OR OTHERWISE DISCLOSED IN PART OR IN WHOLE TO THIRD PARTIES OR USED FOR ANY OTHER PURPOSE WITHOUT PRIOR ECCO WRITTEN CONSENT. ECCO RESERVES ALL PATENT, COPYRIGHT, TRADEMARK AND OTHER PROPRIETARY RIGHTS TO THIS DOCUMENT, INCLUDING ALL DESIGN, MANUFACTURING, REPRODUCTION, USE AND SALES RIGHTS THERETO. THIS DRAWING IS SUBJECT TO RECALL BY ECCO AT ANY TIME, AND YOUR POSSESSION AND/OR USE CONSTITUTES ACCEPTANCE OF THESE TERMS. ©2019 ELECTRONIC CONTROLS COMPANY

SCALE 1:1.75		APPROVALS	DATE
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED: 01		Dr Annie Braithwaite	2019-11-12
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:		CHECKED ABB	
MILLIMETERS DECIMALS XX ± 1.0mm XX.X ± 0.5mm	INCHES DECIMALS X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	MECH. ENG. JLA	
	ANGLES ± 0.5°	ELEC. ENG. SPO	
	FRACTIONS ± 1/64	TEST ENG.	
THIRD ANGLE PROJECTION		SALES. ARS	
		ECCO ® www.eccolink.com Americas (800) 635-5900 Europe +44 (0)113 237 5340 Asia Pacific +61 (0)3 63322444	
		MD LED, 4 LED FLOOD W/ DRL, 12-24V	
CUSTOMER PART NO. CW3007-F		PRODUCT SERIES: CW3006	
SIZE: A	DWG. NO. CW3007-F	REV. 02	
Electronically Controlled Use Latest Copy		SHEET 1 OF 1	Project: EL0145 Date Created: 2019-08-27

REVISION HISTORY		
REV.	DESCRIPTION	DATE
01	PRELIMINARY RELEASE PER EL0145	2019-08-27
02	REVISED PER EL0145	2019-11-12

SPECIFICATIONS

1. CERTIFICATIONS: **CE**; IP67
Note: Unique components, accessories, and hardware kits are not typically included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.
2. RAW LUMENS: 1022 lumens
3. EFFECTIVE LUMENS: 984 lumens
4. ILLUMINANCE (@100 FT): 21 lux
5. PEAK BEAM INTENSITY: 19504 candela
6. VOLTAGE (NOMINAL): 12-24 VDC
7. VOLTAGE (EXTREME): 9-32 VDC
8. CURRENT (PEAK): 1.0A (@ 12 VDC NOMINAL)
9. POWER (MAXIMUM): 13.1W (@ 12 VDC NOMINAL)
10. TEMPERATURE RANGE: -40°F (-40°C) TO 149°F (65°C)
11. CONNECTION: 3 CONDUCTOR CABLE
12. MOUNTING: BRACKET
13. HOUSING MATERIAL: ALUMINUM
14. LENS MATERIAL: POLYCARBONATE
15. PRODUCT WEIGHT: 1.3 LBS (0.59 Kg)