



## LIGHTBARS



## PURSUIT™ - 25 SERIES

### Two levels Of Lighting

The Pursuit™ is uniquely designed with two complete levels of lighting in the height of a single-level lightbar. It features an integrated lens sealing system, encapsulated control electronics, internal wiring channels, auto dimming with photocell, and selectable dimming levels for each light. The C3 Pro™ interface programming allows for an unlimited number of flash pattern options that can be previewed on a PC before being transmitted to the Pursuit™.

### Features

- Two complete levels of lighting in the height of a single-level, 3" high lightbar
- Upper level LED color options:
- Lower level LED color options:
- Powerful lower level LEDs for use as takedown, alley, rear arrowstik, flashing and intersection lights
- C3 Pro™ interface PC programming for an unlimited number of configuration options
- Corner intersection sweeping flash pattern
- Serial network control: Thin, flexible wiring harness

### Options

- Length options - 24", 30", 36", 42", 47", 53", 59", 71", and 77"
- Upper lenses available in red, blue, amber or clear
- Internal illuminated sign module length options - 36", 47", 59"

### Adjustable Mounting Kits

MODEL	WEIGHT	VERTICAL ADJUSTMENT
ADM25KIT	3.3 lbs	0.625"
ADM25LOWKIT	3.3 lbs	0.300"

- Universal, low-rise fit that allows a lightbar to be adjusted to perfectly match the contours of today's emergency vehicles
- The adjustable mounting feet are pursuit speed tested (extra brackets are not required to meet pursuit speed rating)
- The bracket system allows the lightbar to be adjusted for height and front/back angle to ensure the lightbar is perfectly level

Precisely adjust the lightbar here



## PURSUIT™ - 25 SERIES

### Standard Configurations

#### CUSTOM CONFIGURATIONS AVAILABLE ON C3VUE

UPPER MODULE COLOR OPTIONS

LOWER MODULE COLOR OPTIONS

**12-24V | 26 FP + UNLIMITED CONFIGURABILITY**  
3" H x 13.45" D

MODEL	LENGTH	CHASSIS DIAGRAM
25-30251-C	47"	
25-30032-C	47"	
25-30252-C	53"	
25-30253-C	53"	

Call Code3 For Additional Configurations