

To,

The Additional Chief Conservator of Forest (C), Ministry of Environment, Forests & Climate change, 4th Floor, E&F Wing, Kendriya Sadan, Koramangala, Bangaluru-560 034. Date : 22<sup>nd</sup> November 2023 From : P&G Health Limited

Usgaon, Goa

Letter No.: HSE/23/61

Subject: Six monthly compliance reports (for the period of 01.04.2023 to 31.09.2023)

Reference: MoEF No. J-11011/1311/2007-IA-II (I) dated 11.02.09 (Expansion of bulk drug unit at Plot no. 11, Marvasodo, Usgaon, Ponda, Goa by M/s. Merck Limited — Environmental Clearance reg.)

Dear Sir/Madam,

We are sending herewith six-monthly compliance reports (for the period 01.04.2023 to 31.09.2023) for your kind perusal. We are also attaching compilation of reports carried out during the period as annexures. Please find below the other details required by you. Name & contact details of the responsible person:

Name: Mr. Yugit Bansal, Sr. Director Goa Plant

Address: Plot no. 11/1, Marvasodo, Usgaon, Goa - 403407.

Email: bansal.y@pg.com Phone: 0832 2347105

Company Website: https://www.pghealthindia.com/

Thanking you.
Yours faithfully.
For PROCTER & GAMBLE HEALTH LIMITED

Signature of authorized signatory

Encl: a/a CC: 1. Additional Director (MoEF, New Delhi)
2. Goa State Pollution Control Board, Panaji.

Registered Office:

Procter & Gamble Health Limited
CIN: L99999MH1967PLC013726
Godrej One, 8<sup>th</sup> Floor, Pirojshanagar,
Eastern Express Highway, Vikhroli East,
Mumbai 400 079 | Tel: (91-22) 6866 9000

Site Address:

Procter & Gamble Health Limited CIN: L99999MH1967PLC013726 Usgaon, Ponda Taluka, Goa 403 407 | Tel: (91-832) 2347105 www.pghealthindia.com

# Six Monthly Compliance Report

For the Period of 1st April 2023 to 30th September 2023 (22.11.2023)

2

Company Name: Procter & Gamble Health Limited Address: Plot No.11, Marwasodo Usgaon, Ponda - Goa

## Annex- 1

	The second secon	The second secon
Α	SPECIFIC CONDITIONS	
Condition		Compliance Status for the Period of 1st
No	Points	April 2023 to 30th September 2023
		The Effluent Treatment Plant is available. The
	Ine project authorities shall install the effluent treatment plant to treat the	Daily analysis is done at in-house laboratory
-	(GSPCB). The company shall regularly monitor the treated wastewater guality	& monthly basis from MoEF recognised
',	and the reports shall be submitted to the Ministry's Regional Office at Bangalore	laboratory. The copy of monthly analysis
	and GSPCB	report is submitted to GSPCB on monthly
		basis. Online monitoring system for treated
		effluent is available. Refer Annexure-1
		Tank of capacity 180 m <sup>3</sup> is available for
		holding raw effluent & two tanks of capacities
	The company shall provide quard pond for treated wastewater. Bioassay test	220 m <sup>3</sup> each are available to hold neutralised
=	and toxicity index test shall be carried out regularly for the wastewater before	effluent. Treated wastewater sampling is
/	and after treatment and record shall be submitted with the six-monthly reports	done for Bioassay test (toxicity test) on
		monthly basis from MoEF approved lab.
		Compiled data of the same is attached
		herewith. Refer Annexure -1.
	The water requirement and wastewater generation shall not exceed 707 KLD	At present water consumption is around 600
iii)	and 416 KLD respectively. The treated wastewater shall be utilised for green belt development and zero discharge shall be maintained from the plant premises	KLD & wastewater generation is approx. 260 KLD. The treated water is used for green belt
	מסייסיסיחיסיור מוזע בסיס מוסטומו אַכ סומוו אַכּ ווומווומווופט ווסווו נווכ סומוו סיסווווספס.	purpose.
₹	The project authorities shall provide the chilled brine solution in secondary condenser for condensation of the VOCs and ensure that the solvent recovery	All the secondary condensers are provided with chilled water / brine solution for reducing
	shall not be less than 98%.	checked for recovery (98 - 99%).

<	The company shall provide the monitoring arrangement with vents and regular monitoring shall be carried out and reports submitted to the SPCB, CPCB and Ministry's Regional Office at Bangalore.	Vents monitoring are carried out as per consent condition and report submitted to GSPCB. <b>Refer</b> <i>Annexure</i> -2
vi)	To prevent solvent loss, following measures shall be taken: -	
<b>vi)</b> A)	Reactor shall be connected to chilled brine condenser system.	Reactors are connected to chilled water/ brine condenser.
<b>vi)</b> B)	The condensers shall be provided with sufficient HTA and residence time so as to achieve more than 98% recovery.	The condensers are provided with sufficient HTA and residence time to achieve more than 98% recovery.
<b>vi)</b> C)	Solvents shall be stored in a separate space specified with all safety measures.	Solvents are stored in a separate /dedicated area with safety measures as per the requirement under petroleum act. Solvent detection system & automatic sprinkler system is in place.
<b>vi)</b> D)	Proper earthing shall be provided in all the electrical equipment wherever solvent handling is done.	All the electrical equipments are provided with earthing wherever solvent handling is done.
vi) E)	Entire plant shall be flame proof. The solvent storage tanks shall be provided with breather valve to prevent losses.	Flame proof area has been defined & marked on location. Manufacturing of Vitamin E acetate & Oxynex ST has been discontinued & equipment are dismantled. No solvent storage is done in tanks.
vii)	The process emissions VOCs and particulate matter from various units shall conform to the standards prescribed by the concerned authorities from time to time. At no time, the emission levels shall go beyond the stipulated standards. In the event of failure of pollution control system(s) adopted by the unit, the unit shall be immediately put out of operation and shall not be restarted until the desired efficiency has been achieved.	The process emissions VOC & SPM monitoring has been carried out. refer - <b>Annexure -3</b> Emergency operation procedure is in place.
viii)	Fugitive emissions in the work zone environment, product and raw-materials storage area shall be regularly monitored. The emission shall conform to the limits imposed by GSPCB.	Solvent online detection system is provided in solvent storage areas. Fugitive emission monitoring is carried out in store area- refer <i>Annexure -3</i>

ix)	For control of fugitive emission and VOCs following steps shall be followed: -	
ix) A)	Closed handling system shall be provided for chemicals.	Close handling system provided
ix) B)	Reflux condenser shall be provided over reactor.	Reflux condenser is provided over reactor.
ix) C)	Solvent handling pump shall be provided with mechanical seals to prevent leakages.	All the solvent handling pumps provided with mechanical seal.
ix) D)	System of leak detection and repair of pump/pipeline based on preventive maintenance.	Solvent leak detection system in place. Developed Standard Operating Procedure for Preventive maintenance / repair is available.
ix) E)	Solvent shall be taken from underground storage tanks to reactors through closed pipeline. Storage tanks shall be vented through trap receiver and condenser operated on chilled water.	Manufacturing of Vitamin E acetate & Oxynex ST has been discontinued & equipment are dismantled. No solvent storage tanks are available at site.
<b>×</b>	The hazardous wastes generated from the plant shall be disposed of in accordance with the Hazardous Waste (HW) of (Management and Handling) Rules 1989 and as amended. The company shall submit the copy of membership to CHWTSDF (Common Hazardous Waste Treatment Storage and Disposal Facility) to the Ministry's Regional Office at Bangalore.	Hazardous waste is handled and disposes as per Hazardous Waste Rule. Refer <i>Annexure</i> - 4
xi)	During transfer of materials, spillages shall be avoided, and garland drains be constructed to avoid of accidental spillages with domestic waste and storm drains.	Bund wall has been made to protect the accidental spillages with domestics and storm drain.
xii)	The project authorities shall develop greenbelt in 18 acres out of total 37 acres as per guidelines of CPCB to mitigate the effect of fugitive emission.	Total 18 acres green belt is developed out of total 37 acres area to mitigate the effluent discharge.
xiii)	Adequate financial provision shall be made in the budget of the project for implementation of the above suggested environment safeguard. Fund so earmarked shall not be diverted for any other purposes.	Adequate budget / financial provision made for environmental management. Budget for 2023-24: Rs. 60,00,000/-
xiv)	The company shall make adequate arrangement for control of odour nuisance from the plant premises. There shall be no odour from the unit.	The manufacturing facility is made as per GMP requirement & in close ventilation system. There is no odour nuisance from the plant premises.
XV)	Occupational health surveillance of the workers shall be done on a regular basis and records maintained as per the Factories Act.	Occupational health surveillance of workers is carried out annually as per Factories Act.

Ł

XX)	xix)	xviii)	xvii)	vvi)
Provision shall be made for housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, Safe drinking water, medical health care, creche etc. The housing may be in the form of temporary structures to be removed after the completion of the project.	The company shall make the arrangement for protection of possible fire hazards during manufacturing process in material handling.	The company shall strictly all the recommendations mentioned in the charter on Corporate Responsibility for (CREP) For Environmental Protection (CREP) for bulk drug & chemical units.	Usage of PPEs by all employees/ workers shall be ensured.	Training shall be imparted to all employees on safety and health aspects of chemicals handling. As informed to the Ministry, OHSAS 18001 shall be continued. Pre-employment and routine periodical medical examinations for all employees shall be undertaken on regular basis. Training to all employees on handling of chemicals shall be imparted.
All provisions are made as and when required.	Fire Protection system /Fire detection system have been installed. Inertisation of the reactors done by purging nitrogen.	CREP recommendations are followed. Water consumption reduction & Waste minimisations steps are taken at plant level. Waste segregated as per the category.	Usage of PPE's are ensured through SOP/PPE matrix & instruction signs displayed at relevant areas etc.	P&G internal HSE standards equivalent to OHSAS 18001 are implemented at site. Preemployment & routine medical examination is done for all employees. Regular training programmes are conducted on handling of chemicals.

В	GENERAL CONDITIONS	
Condition No	Particulars	Status
<b>.</b>	The project authorities shall strictly adhere to the stipulations of the SPCB/state government or any statutory body.	All the stipulations of the SPCB / State Govt or any other statutory body shall strictly adhere
II)	No further expansion or modifications in the plant shall be carried out without prior approval of the Ministry of Environment and Forests. In case of deviations or alterations in the project proposal from those submitted to this Ministry for clearance, a fresh reference shall be made to the Ministry to assess the adequacy of conditions imposed and to add additional environmental - protection measures required, if any.	For further expansion or modification, prior approval will be taken from MOEF.

viii)	vii)	vi) E)	<b>vi)</b> D)	<b>vi)</b> C)	<b>vi)</b> B)	<b>vi)</b> A)	<b>⊻</b> j)	<u> </u>	<u> </u>	ii)
The overall noise levels in an around the plant area shall be kept well within the standards (85 dBA) by providing noise control measures including acoustic hoods, silencers, enclosures etc. on all sources of noise generation. The ambient noise levels shall conform to the standards prescribed under Environment (Protection) Act, 1986 Rules, 1989 viz. 75 dBA (day time) and 70 dBA (night time).	The project authorities must strictly comply with the rules and regulations with regard to handling and disposal of hazardous wastes in accordance with the Hazardous Waste (Management and Handling) Rules, 2003. Authorization from the SPCB shall be obtained for collections/treatment/storage/disposal of hazardous wastes.	Use of "Closed Feed" system into batch reactors.	Use of automated material transfer system to minimize spillage.	Maximizing recoveries.	Reuse of by-products from the process as raw materials or as raw material substitutes in other processes.	Metering of quantities of active ingredients to minimize waste.	The company shall undertake following Waste Minimization measures: -	For control of process emissions, stacks of appropriate height as per the Central Pollution Control Board guidelines shall be provided. The scrubbed water shall be sent to ETP for further treatment.	Ambient air quality monitoring stations shall be set up in the downwind direction as well as where maximum ground level of concentration are anticipated in consultation with the State Pollution Control Board.	The project authorities shall strictly comply with the rules and regulations under Manufacture, Storage, and Import of the Hazardous Chemicals Rules, 1989 as amended. Authorization from the SPCB shall be obtained for collection, treatment, storage, and disposal of hazardous wastes.
Noise levels are monitored through calibrated Noise level meter and monitoring records are kept in Register. <b>Refer Annexure -5</b>	Hazardous wastes are handled and dispose as per Hazardous Waste Rule. Authorisation is obtained from Goa State Pollution Control Board. Refer <b>Annexure - 4</b> for hazardous waste disposed during the six months.	Closed Feed system is available in the batch reactors.	Used Powder Charging system to minimize manual handling and spillage. Close loop feeding is followed.	Chilled /brine in secondary condenser available for maximizing recoveries.	By products from the process are reused /recycled	Waste generations are monitored		Stack height of Boiler is 33 mt. Other stacks are maintained as per consent conditions. Scrubber wastewater is treated through ETP.	Ambient air quality monitoring is done by online monitoring system which is connected to CPCB & GSPCB server.	Compliance made as per manufacture, storage and import of Hazardous Chemical Rules. Authorization from the SPCB shall be obtained for collection, treatment, and disposal. As per Hazardous Waste Management &Handling rule 1989. Disposal records manifest copy is available.

9.0	8.0	7.0	6.0	xiii)	xii)	Xi)	<b>×</b>	, <del>X</del>
The above conditions shall be enforced, inter-alia under the provisions of the Water (Prevention & Control of Pollution) Act, 1974 Air (Prevention & Control of Pollution) Act, 1981, the Environment (Protection) Act, 1986, Hazardous Wastes (Management & Handling) Rules, 2003 and the Public Liability Insurance Act, 1991 along with their amendments and rules.	Any appeal against this environmental clearance shall lie with the National Environment Appellate Authority, if preferred within a period of 30 days as prescribed under Section 11 of the National Environment Appellate Authority Act, 1997.	The Ministry reserves the right to stipulate additional conditions, if found necessary. The company in a time bound manner shall implement these conditions.	The Ministry may revoke or suspend the clearance, if implementation of any of the above conditions is not satisfactory.	The project authorities shall inform the Regional Office as well as the Ministry, the date of financial closure and final approval of the project by the concerned authorities and the date of start of the project.	The project proponent shall inform the public that the project has been accorded environmental clearance by the Ministry and copies of the clearance letter are available with the SPCB and may also be seen at Website of the Ministry at the http://envfor.nic.in. This shall be advertised within seven days from the date of issue of the clearance letter, at least in two local newspapers that are widely circulated in the region of which one shall be in the vernacular language of the locality of concerned and a copy of the same shall be forwarded to the Ministry's Regional Office.	The implementation of the project vis-à-vis environmental action plans shall be monitored by Ministry's Regional Office of /SPCB / CPCB. A six-monthly compliance status report shall be submitted to monitoring agencies	The project authorities shall provide rainwater harvesting system and ground water recharge.	A separate Environmental Management Cell equipped with full fledged laboratory facilities shall be set up to carry the environmental management and monitoring functions.
Complied.			1	Complied.	Complied.	Six monthly compliance is submitted regularly to MoEF, CPCB & SPCB.	Rainwater harvesting pond for storing about 21600 KL is available with ground water recharging system.	Environmental Management Cell headed by Director and full fledge environmental laboratory facility is available.

	,	.,		<b>,</b>	<del>,</del>		,		
Sep-23	Aug-23	Jul-23	Jun-23	May-23	Apr-23	Legal Consent Limits As per- Goa State Pollution Board	Parameters		
6.66	7.31	7.02	6.13	6.97	6.35	6 - 8.5	Ŧ		
68	76	88	76	88	72	250	COD mg/lit		۰
15.3	19.95	17.76	19	18.8	15.3	30	COD mg/lit BOD mg/lit TSS mg/lit		
44	39	. 45	41	45	39	100	TSS mg/lit		
1.2	1.4	2	2.4	2	2	10	O&G mg/lit		
۵	۵	۵	۵	۵	۵	2	Sulphide as S2- mg/lit		
<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	£4.	Phenolics compound mg/lit		
<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.1	Hexavalent chromium as Cr+6 mg/lit		
45,92	47.6	45.36	39.2	42.56	45.92	100	Ammonical Nitrogen mg/lit		Wate
ND	ND	ND	ND	ND	ND	0.1	Benzene mg/lit	Effluent	r Analysi
ND	ND	ND	ND	ND	ND	0.12	Xylene mg/lit	Treated v	s of Rav
ND	ND	ND ND	ND	ND	ND	0.9	Methylene Chloride mg/lit	<b>Effluent Treated water Analysis</b>	//Treate
ND	NO	ND	ND	ND	ND	0.2	Chlorobenzene mg/lit	lysis	Water Analysis of Raw / Treated Effluent - Apr
0.75	0.75	0.61	0.49	0.62	0.73	Less than 26 (applicable only for discharge on land)	SAR mg/lit		•
0.17	0.24	0.18	0.22	0.17	0.21	55	Zinc mg/lit		23 to :
0.09	0.12	0.07	0.04	<0.01	<0.01	ε	Copper mg/lit		2023 to Sep 2023
<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	2	Total Chromium mg/lit		ω
0.01	0.01	0.01	0.01	0.01	<0.01	0.1	Cyanide as CN* mg/lit		
2.14	2.15	Δ	4	4	4	5	Cyanide as Phosphate Arsenic Lead CN* mg/lit as P mg/lit mg/lit mg/lit		
<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.2	Arsenic mg/lit		
<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.1	Lead mg/lit		
<0.001	<0.001	<0.001	<0.001	<0.001	<0.001	0.01	Mercury mg/lit		
90% survival for 96hrs	90% survival of fish after 96hrs in 100% effluent	Bio-Assay test							
7.87	5.86	5	6.4	5.6	6.6		P	Et	
920	2560	2400	712	1680	1328		COD mg/lit	fluent R	
200	766	699	172	525	334		COD BOD TSS O&G	Effluent Raw water Analysis	
276	269	243	257	245	210		TSS mg/lit	r Analy:	
9.4	8	7	7		00		O&G mg/lit	sis	

## Annexure 2

Stack monitoring report - Apr 2023 to Sept 2023 - Frequency of Monitoring is Quarterly

					-
Sr No.	Area	Parameters	Legal Limits as per Pollution Control Board	Apr-23	Jul-23
		Sulfuric Acid Mist mg/M <sup>3</sup>	NA	<0.10	<0.10
1	QC scrubber no 1	Hydrochloric Acid Mist mg/M <sup>3</sup>	NA	<0.10	<0.10
		Nitric Acid Mist mg/M³	NA	<0.10	<0.10
2	QC scrubber no 2	Ether mg/M <sup>3</sup> Methanol mg/M <sup>3</sup>	NA NA	<0.10 <0.10	<0.10
3	Dust collector 1(VIT E Dry Powder & Food Premix )	PM	NA	32.84	27.21
4	TDS Scrubber stack	HCL mg/m3	NA	1.5	NA
		Particulate matter g/Kw-hr	0.3	0.13	0.14
5	DG set Stack- 500KVA(Sr No	SO2 kg/hour Nox g/kw-hr	9.2	0.13	0.12
	07/0804/0198)	CO g/kw-hr	3.5	0.08	0.07
		Carbon Dioxide %	NA 1.2	11.4	11.2
		HC g/kw-hr	1.3	0.05	0,06
		Particulate matter g/Kw-hr	0.3	0.13	0.14
6	DG set Stack- 500KVA(Sr No	SO2 kg/hour	2.1 9,2	0.12	0.13
ŭ	07/0804/0199)	Nox g/kw-hr CO g/kw-hr	9,2 3.5	0.14	0.16
		Carbon Dioxide %	NA NA	11.3	10.6
		HC g/kw-hr	1.3	0.06	0.05
		Particulate matter	0.3	0.15	0.13
		g/Kw-hr			
-	DG set Stack new-500 KVA(Sr No	SO2 kg/hour	2.1	0.12	0.14
7	07/1109/01149)	Nox g/kw-hr Carbon Dioxide %	9.2 NA	0.24 11.2	0.33 11.5
		CO g/kw-hr	3.5	0.09	0.08
		HC g/kw-hr	1.3	0.06	0.07
		Particulate matter g/Kw-hr	0.3	0.12	0.14
	DG set (750KVA) (Stack 1) (25420923)	SO2 kg/hour	3.15	0.14	0.12
8	(sr.no. 07/1612/0423)	Nox g/kw-hr	9.2	0.4	0.23
		Carbon Dioxide % CO g/kw-hr	NA 3.5	0.08	0.09
		HC g/kw-hr	1.3	0.07	0.07
		Particulate matter	0.3	0.15	0.14
	DG set (750KVA) (Stack 2)	SO2 kg/hour	3.15	0.14	0.12
9	(25420923)(sr.no. 07/1612/0423)	Nox g/kw-hr	9.2	0.38	0.21
		Carbon Dioxide %	NA 3.5	11.6	11.6
		CO g/kw-hr HC g/kw-hr	1.3	0.1 0.07	0.09
		Particulate matter	0.3	0.15	0.13
	DC ant /750(0)(A) (Shorth 1) Navy Janua	SO2 kg/hour	3.15	0.13	0.11
10	DG set (750KVA) (Stack 1) New (sr.no. 07/1604/0014) 25415671	Nox g/kw-hr	9.2	0.16	0.14
	37,1004,0014,15415071	Carbon Dioxide %	NA	11.2	11.1
		CO g/kw-hr	3.5	0.07	0.08
		HC g/kw-hr Particulate matter	0.3	0.05	0.06
		g/Kw-hr		0.12	0.12
11	DG set (750KVA) (Stack 2) (Sr.No.	SO2 kg/hour Carbon Dioxide %	3.15 NA	0.13 11.4	0.12 11.2
	07/1604/014) 25415671	Nox g/kw-hr	9.2	0.18	0.12
		CO g/kw-hr	3.5	0.08	0.07
		HC g/kw-hr	1.3	0.06	0.04
		Particulate matter g/Kw-hr	0.3	0.13	0.14
	DG set (750KVA) (Stack 1) New (sr.no.)	SO2 kg/hour	3.15	0.15	0.13
12	(25421685)	Nox g/kw-hr	9.2	0.22	0.18
	•	Carbon Dioxide %	NA 3.5	11.4	11.3
		CO g/kw-hr HC g/kw-hr	1.3	0.08	0.08
		Particulate matter	0.3	0.13	0.14
	DG set (750KVA) (Stack 2) New (sr.no.)	SO2 kg/hour	3.15	0.12	0.13
13	(25421685)	Nox g/kw-hr	9.2	0.36	0.17
	,,	Carbon Dioxide %	NA 2.5	11.5	11.7
		CO g/kw-hr HC g/kw-hr	3.5 1.3	0.09	0.07
		Particulate matter	0.3	0.12	
		SO2 kg/hour	NA	0.04	Under
14	Fire Diesel Pump Stack	Nox g/kw-hr	9.2	0.18	inspection/ maintenanc
		Carbon Dioxide %	NA	11.2	e
		CO g/kw-hr	3.5	0.07	
		HC g/kw-hr Particulate matter	1.3	0.05	
15	Boiler (6 TPH)	mg/Nm3 SO2 kg/hour	800 NA	178.47 0.44	161.24 0.38
16	Boiler (4 TPH)	Particulate matter mg/Nm3	800	159.93	Under inspection/ma
		SO2 kg/hour	20.32	0.33	intenance
					·

## Annexure 3

	Workplace Monitoring Repo	rt	
	Apr 2023 to Sep 2023		
Sr No	Area	Parameter with Units	Apr-23
		VOC ppm	<1.0
4	DOLLAR (Six magnitud)	HCL mg/m3	<1.0
1	Work place monitoring- PPI Lab (Six monthly)	NH3 ug/m3	<20.00
		HC ppm	<0.001
2	Wall of a maritarian Day Day day (Six manthly)	PM10 mg/m3	0.05
2	Work place monitoring- Dry Powder (Six monthly)	PM2.5 mg/m3	0.021
3	Work place monitoring- TDS production (Six monthly)	VOC ppm	<1.0
***		PM10 mg/m3	0.057
		PM2.5 mg/m3	0.025
		SO2 mg/m3	<0.003
4	Work place monitoring- Chemical RM store (Six monthly)	NOX mg/m3	<0.006
		CO mg/m3	0.04
		PHAs PPM	<0.001
		Toluene/Xylene PPM	<0.01
5	Work place monitoring- DP Godown (Six monthly)	VOC PPM	<1.0
	Ward along required FTD lime bouse (Six monthly)	PM10 mg/m3	0.051
6	Work place monitoring- ETP lime house (Six monthly)	PM2.5 mg/m3	0.022
		VOC PPM	<1.0
7	Wark place manitaring OC (Six monthly)	HCL mg/m3	<1.0
7	Work place monitoring- QC (Six monthly)	NH3 ug/m3	<20.00
		HC ppm	<0.001
	Mark place provide ving Dhouse DM store (Six provide)	PM10 mg/m3	0.048
8	Work place monitoring- Pharma RM store (Six monthly)	PM2.5 mg/m3	0.019

Haz Waste Manifest Apr 2023 to Sep 2023

Annexure 5
Ambient Noise level Apr 2023 to Sep 2023

) leq	$\rfloor_{f D}$	Ambient Noise level Monitoring Report Day time	el Monitoring R	Report Day time
Noise in dB (A) leq (Day time) Legal Limits 75  Near Main gate 55.1  Near Injection plant 56.7  Near Oxynex ST plant 58.5  Near Soft gel 54.4  Near boiler 72.8			Apr-23	5Z-m
Legal Limits(Day time)Near Main gate55.1Near Injection plant56.7Near Oxynex ST plant58.5Near Soft gel54.4Near GZ55.3Near boiler72.8			Noise in dB (A) leq	Noise in dB (A) leq
Legal Limits75Near Main gate55.1Near Injection plant56.7Near Oxynex ST plant58.5Near Soft gel54.4Near GZ55.3Near boiler72.8			(Day time)	(Day time)
Near Main gate55.1Near Injection plant56.7Near Oxynex ST plant58.5Near Soft gel54.4Near GZ55.3Near boiler72.8		Legal Limits	75	75
Near Injection plant56.7Near Oxynex ST plant58.5Near Soft gel54.4Near GZ55.3Near boiler72.8	1	Near Main gate	55.1	57.5
Near Oxynex ST plant58.5Near Soft gel54.4Near GZ55.3Near boiler72.8	2	Near Injection plant	56.7	59.4
Near Soft gel54.4Near GZ55.3Near boiler72.8	ω	Near Oxynex ST plant	58.5	59.3
Near GZ 55.3  Near boiler 72.8	4	Near Soft gel	54.4	55.1
Near boiler 72.8	5	Near GZ	55.3	53.2
	6	Near boiler	72.8	73

Moise in dB (A) leq (Noise in dB (A) leq (Night time) (N legal Limits 70 1 Mear Main gate 51.2 Near Injection plant 52.3 Near Oxynex ST plant 54.6 Near Soft gel 49.1 50.3 Near boiler 68.7	Am	<b>Ambient Noise level Monitoring Report Night time</b>	<b>Monitoring Rep</b>	oort Night time
Noise in dB (A) leq (Night time)  Legal Limits 70  Near Main gate 51.2  Near Oxynex ST plant 54.6  Near Soft gel 49.1  Near GZ 50.3  Near boiler 68.7			52-10V	5000 5000 5000 1000 10000 10000 10000 10000 10000 10000 10000 10000 10000 10000 1000
Legal Limits  Near Main gate  Near Injection plant  Near Oxynex ST plant  Near Soft gel  Near GZ  Near boiler			Noise in dB (A) leq (Night time)	Noise in dB (A) leq (Night time)
Near Main gate  Near Injection plant  Near Oxynex ST plant  Near Soft gel  Near GZ  Near boiler		Legal Limits	70	70
Near Injection plant Near Oxynex ST plant Near Soft gel Near GZ Near boiler	ы	Near Main gate	51.2	52.4
Near Oxynex ST plant  Near Soft gel  Near GZ  Near boiler	2	Near Injection plant	52.3	51.7
Near Soft gel  Near GZ  Near boiler	ω	Near Oxynex ST plant	54.6	53.8
Near GZ Near boiler	4	Near Soft gel	49.1	51.1
Near boiler	5	Near GZ	50.3	48.7
	6	Near boiler	68.7	67.9

## Annexure 6 Site Ambient air quality report Apr 2023 to Sep 2023

				Ambie	nt Ambien	<b>Ambient Ambient air quality report Near</b>	y report N	ear ETP				
Month/ Parameters	PM10 µg/m3	PM2.5 µg/m3	PM10 µg/m3 PM2.5 µg/m3 SO2 µg/m3 NOX µg/m3	<u> </u>	Ammonia (NH3) µg/m3	CO µg/m3	Lead (Pb) µg/m3	Benzene(C6H6) µg/m3	Arsenic (As) µg/m3	Nickel(Ni) µg/m3	О3 µg/m3	Benzo(a) Pyrene Ng/M3
Limits (For 24 Hrs)	100	60	80	80	400	4	-1	5	6	20	180	ы
Apr-23	76.53	24.74	4.4	10.09	<20.00	<0.20	<0.10	<1.00	<5.00	<5.00	<20.00	<0.20
Jul-23	32.82	11.39	<3.00	<6.00	<20.00	<0.20	<0.10	<1.00	<5.00	<5.00	<20.00	<0.20
Annual Average	54.675	18.065	4.4000	10.0900	#DIV/0!	#DIV/0!	i0/AlG#	#DIV/0!	#DIV/0!	#DIV/0!	#DIV/0!	#DIV/0!
												***************************************

			·	Т		
Annual Average	Jul-23	Apr-23	Limits (For 24 Hrs)	raidilleteis	Month/	
64.79	38.77	90.8	100	µg/m3	PM10	
21.17	14,47	27.86	60	µg/m3	PM2.5	
3.95	<3.00	3.95	80	µg/m3	SO2	
9.66	<6.00	9.66	80	µg/m3	NOX	Ambient a
#DIV/0!	<20.00	<20.00	400	µg/m3	Ammonia (NH3)	ir quality
#DIV/0!	<0.20	<0.20	4	mg/m3(L)	co	report Nea
#DIV/0!	<0.10	<0.10	_	µg/m3	Lead (Pb)	Ambient air quality report Near Main Securi
#DIV/0!	<1.00	<1.00	٥,	µg/m3	Benzene(C6H6) Arsenic (As)	curity Gate
#DIV/0!	<5.00	<5.00	6	µg/m3		
#DIV/0!	<5.00	<5.00	20	µg/m3	Nickel(Ni)	
#DIV/0!	<20.00	<20.00	180	μg/m3	03	
#DIV/0!	<0.20	<0.20	<b></b>	Ng/M3	Benzo(a) Pyrene	

#DIV/0!	i0/AlG#	#DIV/0!	#DIV/0!	#DIV/0!	i0/Aid#	10//VID#	#DIV/0!	7.80	3.56	19.77	53.98	Annual Average
<0.20	<20.00	<5.00	<5.00	<1.00	<0.10	<0.20	<20.00	<6.00	<3.00	12.64	30.28	Jul-23
<0.20	<20.00	<5.00	<5.00	<1.00	<0.10	<0.20	<20.00	7.8	3.56	26.9	77.68	Apr-23
ц	180	20	6	5	_	4	400	80	80	60	100	Limits (For 24 Hrs)
Ng/M3	µg/m3	µg/m3	µg/m3	рд/т3	µg/m3	mg/m3(L)	µg/m3	µg/m3	µg/m3	µg/m3	µg/m3	rdidilleters
Benzo(a) Pyrene	03	Nickel(Ni)	Arsenic (As)	Benzene(C6H6)	Lead (Pb)	со	Ammonia (NH3)	NOX	S02	PM2.5	PM10	Month/
				el Plant	Near Softg	Ambient air quality report Near Softgel Plant	nt air qua	Ambie				