

# MindConnect Nano

## Product Sheet and Specific Terms



MindConnect Nano is a device for transferring data and allows connectivity to MindSphere. Different protocols are supported in order to collect data. The device supports transmission of data through a secure Internet connection to MindSphere to enable cloud-based applications and services. MindConnect Nano can only be used in conjunction with MindSphere.

### Functions

Field protocol – S7	Siemens S7 Put/Get Access (for all S7 PLCs as non-symbolic addressing)
Field protocol – OPC UA	OPC UA Client (Data Access)
Field protocol – Modbus	Connections to Modbus devices via TCP/RTU
Field protocol – EtherNet/IP	Connections to EtherNet/IP devices
Configuration of data collection	With Asset Configuration tool in MindSphere
Data buffering	Up to 500 MB buffering space for collected data
Proxy Support	Yes
DHCP Support	Yes
Security	Connection outbound via HTTPS on port 443 to MindSphere only; no incoming connection accepted; SSL/TLS encryption of data in transit to MindSphere

### Installation Type/Mounting

Mounting	DIN rail, wall mounting, portrait mounting
Design	IoT Gateway, Built-in unit

## Supply Voltage

Type of supply voltage	24 V DC
Mains buffering	
Mains/voltage failure stored energy time	20 ms

## Processor

Processor type	Intel Celeron N2807
----------------	---------------------

## Drives

Hard disk	CFast 4 GB
-----------	------------

## Memory

Type of memory	DDR3L
Main memory	2 GB

## Interfaces

USB port	1x USB 2.0
PCIe slot	1x PCIe x1 (available only in conjunction with MindSphere)
Serial interface	1x COM (available only in conjunction with MindSphere)
Video interfaces	
Graphics interface	1x DisplayPort (available only in conjunction with MindSphere)
Industrial Ethernet	
Industrial Ethernet interface	2x 1000 Mbit RJ45

## Monitoring Functions

Status LEDs	Yes
Fan	No

## EMC

### Interference immunity against discharge of static electricity

Interference immunity against discharge of static electricity	±6 kV contact discharge acc. to IEC 61000-4-2; ±8 kV air discharge acc. to IEC 61000-4-2
---	---

### Interference immunity to cable-borne interference

Interferences immunity on supply cables	±2 kV acc. to IEC 61000-4-4, burst; ±1 kV acc. to IEC 61000-4-5, surge symmetric; ±2 kV acc. to IEC 61000-4-5, surge asymmetric
---	---

Interference immunity on signal cables > 30 m	±2 kV acc. to IEC 61000-4-5, length > 30 m
---	--

Interference immunity on signal cables < 30 m	±1 kV acc. to IEC 61000-4-4, burst; length < 3 m; ±2 kV acc. to IEC 61000-4-4, burst; length > 3 m
---	---

### Interference immunity against voltage surge

asymmetric interference	±2 kV acc. to IEC 61000-4-5, surge asymmetric
-------------------------	---

symmetric interference	±1 kV acc. to IEC 61000-4-5, surge symmetric
------------------------	--

### Interference immunity against high-frequency electromagnetic fields

Interference immunity against high-frequency radiation	10 V/m for 80 – 1 000 MHz and 1.4 – 2 GHz, 80% AM acc. to IEC 61000-4-3; 3 V/m for 2 – 2.7 GHz, 80% AM acc. to IEC 61000-4-3; 10 V for 10 kHz – 80 MHz, 80% AM acc. to IEC 61000-4-6
--	--

### Interference immunity to magnetic fields

Interference immunity to magnetic fields at 50 Hz	100 A/m; to IEC 61000-4-8
---	---------------------------

### Emission of conducted and non-conducted interference

Interference emission via line/AC current cables	EN 61000-6-3, EN 61000-6-4, CISPR 22 Class B, FCC Class A
--	---

## Degree and Class of Protection

IP (at the front)	IP40
-------------------	------

IP (rear)	IP40
-----------	------

## Standards, Approvals, Certificates

CE mark	Yes
UL approval	Yes
UL 508	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EMC	CE, EN 61000-6-4:2007, EN 61000-6-2:2005
EN 61000-6-2	Yes
Dust protection	Protection against foreign bodies > 1 mm
FCC	Yes

## Ambient Conditions

### Ambient temperature during operation

Ambient temperature during operation 0 °C up to 60 °C

### Ambient temperature during storage/transportation

min. -20 °C

max. 60 °C

### Relative humidity

Relative humidity Tested according to IEC 60068-2-78, IEC 60068-2-30: Operation: 5% to 80% at 25 °C (no condensation), storage: 5% to 95% at 25 °C (no condensation)

### Vibrations

Vibration load in operation Tested to DIN IEC 60068-2-6: 10 Hz to 58 Hz: 0.075 mm, 58 Hz to 200 Hz: 9.8 m/s<sup>2</sup> (1 g)

### Shock testing

Shock load during operation Tested according to IEC 60068-2-27: 150 m/s<sup>2</sup>, 11 ms

## Dimensions

Width	191 mm
Height	100 mm
Depth	60 mm

## Support

### Contacting MindSphere Support

For all infrastructure providers	<p>You may contact the MindSphere Support organization as primary point of contact for support.</p> <ul style="list-style-type: none"> <li>• An incident request ID is required to process your request. To receive such ID, an initial incident request has to be created by using the link to a support/ support form or tool provided on your MindSphere Launchpad. The incident request ID will then be sent via email or chat-software.</li> <li>• After receipt of the incident request ID, you will be contacted via email, or phone or chat-software by MindSphere Support. You may also contact the regional 'Global Technical Access Center' (GTAC) organization (except in People's Republic of China). The GTAC country website is available via the following web link: <a href="http://www.siemens.com/gtac">www.siemens.com/gtac</a>.</li> </ul>
----------------------------------	---

### Scope of MindSphere Support

Infrastructure provider	Support language	Operating hours & Support centers
Alibaba Cloud	Chinese On request in English	Monday through Friday 9:00 am to 6:00 pm CST (People's Republic of China, Chengdu) – excluding national and local holidays.
Amazon Web Services	English	Monday through Friday 8:00 am to 5:00 pm CET (Germany, Nuremberg) and CST (USA, Maryland Heights) and 9:00 am to 6:00 pm IST (India, Delhi) – excluding national and local holidays.
Microsoft Azure		

MindSphere Support is available to you remotely for up to one hour per support case. You have to ensure remote access to your local networks for e.g. remote diagnoses.

## Security Information

General	In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial security concept.
---------	--