# **MONIER**





# **MONIER**

#### **Features**

- Absolute flat surface
- High breaking strength: > 220 kg / cm2
- Low water absorption : < 7 %</p>
- Durable mono and antique colours available



## Technical Data

330 mm x 420 mm
5.0 to 5.15 kg
320 mm to 345 mm
10 pcs
25 Degree









### Coverage and unit weight of tiles at various slopes

Slope (in degrees)	Minimum overlapping	Maximum batten space	Number of tiles	Unit weight
>25 and <35	100 mm	320 mm	0.966 / sq.ft	± 4.83 kg / sq.ft
>35	75 mm	345 mm	0.890 / sq.ft	± 4.45 kg / sq.ft

#### **Fittings**

Ridge and Hip

Perfect finishing for your roof



Ridge End




Ridge Tile



Hip Starter








Barge
Aesthetic Way to
protect the top of your walls
and to safely finish your roof








Barge End



















Compact Roll to ventilate ridges and hips

Easyflash for waterproof abutments

Valley Metal Sheet for water orienteering

RadenShield for waterproofing and heat reduction

Shield for for hea proofing reduction

Radiant Barrier Translucent Tile for heat for reduction natural light

Visit our exclusive showroom and orientation center, Monier Roofing Pvt Ltd.

143/C3, Bommasandra industrial area, 1st phase, Bangalore - 560099 Tel: 080 41658016 / 27, Mob: +91 90191 10303, +91 96866 63013 Email: contact.india@bmigroup.com, www.bmigroup.com/in



https://twitter.com/bmimonierindia

Chat @ 90191 10303



**Authorized Roofing Partner**