

## FOR TELECOMMUNICATIONS APPLICATIONS

Capacities from 270 to 720 Ampere-hours

C&D Technologies' flooded batteries are engineered to provide superior performance and reliability over the life of the product. These batteries are designed using proprietary techniques and quality components and materials for reduced maintenance and extended battery life.

**FLOODED**

**12-321-KCT**



### FEATURES & BENEFITS

- Electrical testing (capacity test) on every cell prior to shipping assures performance of every battery upon delivery.
- Proprietary vacuum-assisted, bottom-pour, positive-grid casting assures void-free grid quality resulting in 20 year service life.
- Waterbath charging results in consistently formed plates for reliable performance out of the box (no cycling required in the field).
- Suspended positive plates permit free growth without pressure on jar and cover.

### SAFE OPERATION

Standard flame-retardant covers enhance battery plant safety with self-extinguishing properties, LOI>32%, UL 94V-0.

Low-evaporation, flame-arrester vent to extend watering intervals and prevent external sparks from reacting with the hydrogen inside the cell.

### COST SAVINGS

Transparent container allows visual inspection of plates

Soft rubber post seal minimizes stress on post reducing maintenance requirements

Computer controlled heli-arc welded post seals result in consistent and reliable seals for less maintenance and longer product life

### APPLICATIONS

- Telephone Central Offices
- Mobile Telephone Switching Office
- Cable Head End Sites
- Fiber Optic Regenerator Sites
- Microwave Repeater Sites
- Telephone & Internet Network Nodes

## SPECIFICATIONS

PLATES	HEIGHT	WIDTH	THICKNESS
POSITIVE	11.38 in (289 mm)	8.75 in (222 mm)	0.312 in (7.90 mm)
NEGATIVE	11.38 in (289 mm)	8.75 in (222 mm)	0.210 in (5.30 mm)
OUTSIDE NEGATIVE	11.38 in (289 mm)	8.75 in (222 mm)	0.120 in (3.05 mm)
ELECTROLYTE HEIGHT ABOVE PLATES	2.06 in (52 mm)		
SEDIMENT SPACE	0.75 in (19.1 mm)		
ELECTROLYTE @ + 77°F (+25°C)	Sulfuric acid, 1.215 specific gravity nominal		
RECOMMENDED FLOAT VOLTAGES	2.17 - 2.22 volts per cell (calcium); 2.15-2.18 volts per cell (antimony)		
CONTAINER*	Thermoplastic, transparent, (SAN)		
COVER	High-impact, flame-retardant thermoplastic (PVC), with tongue-and-groove seal. Flammability ratings: UL 94-V0; LOT>32; ASTM D-635 self-extinguishing		
SEPARATOR	Microporous with fibrous glass mat		
SAFETY VENT SYSTEMS	Flame-arrester type		
TERMINALS	Two, 1-inch (25 mm) square posts with two cross-bolt holes		
WITHDRAWAL TUBES, OPTIONAL	Two per cell		
OPTIONAL CONTAINER	Transparent, flame-retardant polycarbonate. Flammability ratings: UL 94-HB; PVC available for KCT-540 only		

MODEL	CELLS PER UNIT	PLATES PER CELL	OVERALL DIMENSIONS			APPROX. WEIGHT LBS (KGS)		ELECTROLYTE PER CELL LBS (KGS)	CPR CODE NUMBER (KCT ONLY)
			L IN (MM)	W IN (MM)	H IN (MM)*	FILLED	PACKED		
KCT-270	1	7	3.62 (91.9)	10.44 (265)	18.25 (464)	57 (25.9)	74 (33.6)	15 (6.8)	162231
KCT-360	1	9	4.62 (117)			77 (34.9)	95 (43.1)	20 (9.1)	569638
KCT-450	1	11	5.59 (142)			94 (42.6)	109 (49.5)	25 (11.3)	169272
KCT-540	1	13	6.59 (167)			111 (50.3)	131 (59.4)	29 (13.2)	169273
KCT-660	1	15	8.53 (217)			136 (61.7)	158 (71.7)	40 (18.1)	063783
KCT-720	1	17	8.53 (217)			143 (64.9)	165 (74.8)	38 (17.2)	269106


Note: Electrolyte weighs approximately 10 lbs per gallon (1.215 kgs per liter).

For information on battery racks, please refer to brochure 12-560.

## RATINGS TABLE: AMPERES

MODEL	8 HR-AH	*NOMINAL RATES @ +77°F (+25°C) IN 1.215 NOMINAL SG (INCLUDES CONNECTION VOLTAGE DROP)								
		1 HR	2 HR	3 HR	4 HR	5 HR	6 HR	8 HR	10 HR	24 HR
KCT-270	270	121	83	66	55	48	42	34	29	14
KCT-360	360	161	111	88	73	63	56	45	39	19
KCT-450	450	201	139	110	92	79	70	57	48	24
KCT-540	540	241	167	132	110	95	84	68	58	28
KCT-660	660	283	199	158	133	116	102	83	71	35
KCT-720	720	321	222	175	147	127	112	90	77	38
KCT-270	264	112	79	62	52	45	40	33	28	14
KCT-360	344	149	105	83	70	60	53	43	37	18
KCT-450	432	187	132	104	87	75	67	54	46	23
KCT-540	520	224	158	125	104	90	80	65	55	27
KCT-660	640	263	189	150	127	110	97	80	68	34
KCT-720	696	299	211	166	139	120	106	87	74	36
KCT-270	248	96	71	57	48	42	37	31	26	13
KCT-360	328	128	94	76	64	56	49	41	35	18
KCT-450	408	160	118	95	80	69	62	51	43	22
KCT-540	488	193	142	113	96	83	74	61	52	26
KCT-660	600	226	169	137	116	102	90	75	64	32
KCT-720	648	257	189	151	128	111	99	81	69	35
KCT-270	232	87	66	53	45	40	35	29	25	13
KCT-360	312	116	88	71	60	53	47	39	33	17
KCT-450	384	144	110	89	75	66	59	48	41	21
KCT-540	464	173	132	107	91	79	70	58	50	25
KCT-660	568	203	157	129	110	96	86	71	61	31
KCT-720	616	231	175	142	121	105	94	77	66	34
KCT-270	216	75	59	49	42	37	33	27	23	12
KCT-360	296	100	79	66	56	49	44	37	31	16
KCT-450	368	125	99	82	70	62	55	46	39	20
KCT-540	440	149	119	98	84	74	66	55	47	24
KCT-660	536	175	142	119	103	90	81	67	57	29
KCT-720	584	199	158	131	112	99	88	73	63	32
KCT-270	208	63	53	45	39	35	31	26	22	11
KCT-360	272	84	70	60	52	46	41	34	29	15
KCT-450	344	105	88	75	65	58	52	43	37	19
KCT-540	408	126	105	90	78	69	62	51	44	22
KCT-660	504	147	125	108	95	85	76	63	53	26
KCT-720	552	167	141	120	104	92	83	69	59	30
KCT-270	177	49	42	37	32	29	26	22	19	10
KCT-360	235	65	56	49	43	39	35	29	26	13
KCT-450	294	82	70	61	54	48	44	37	32	17
KCT-540	354	98	84	74	65	58	53	44	38	20
KCT-660	432	115	100	88	79	71	64	54	47	24
KCT-720	471	131	113	98	87	77	70	59	51	27

# BATTERIES AND RACKS

<b>STEP</b>	<b>RDB0801-(L)</b> <b>TWO TIER</b> (M-11416) WIDTH: 20.9IN (513MM) HEIGHT: 45.88IN (1165MM) (TO TOP OF FRAME)		<b>RDB0803-(L)</b> <b>TWO STEP</b> (M-11422) WIDTH: 37.13IN (943MM) HEIGHT: 35.88IN (911MM) (TO TOP OF FRAME)	
-------------	--	---	--	---

MODEL	NO. OF CELLS	LENGTH (L)		WEIGHT (W)		NO. REQUIRED	NO. OF CELLS	LENGTH (L)		WEIGHT (W)		NO. REQUIRED
		FT	MM	LBS	KGS			FT	MM	LBS	KGS	
KCT-270	12	3	914	113	51	1	12	3	914	132	60	1
	24	5	1524	128	58	1	24	5	1524	146	66	1
KCT-360	12	3	914	113	51	1	12	3	914	132	60	1
	24	6	1829	134	61	1	24	6	1829	152	69	1
KCT-450	12	4	1219	121	55	1	12	4	1219	139	63	1
	24	7	2134	180	82	1	24	7	2134	208	94	1
KCT-540	12	4	1219	121	55	1	12	4	1219	139	63	1
	24	7.3	2225	180	82	1	24	7.3	2225	208	94	1
KCT-660	12	5	1524	128	58	1	12	5	1524	146	66	1
	24	9	2743	193	88	1	24	9	2743	222	101	1
KCT-720	12	5	1524	128	58	1	12	5	1524	146	66	1
	24	9	2743	193	88	1	24	9	2743	222	101	1

World Headquarters  
 200 Precision Road  
 Horsham, PA 19044 USA  
 T: +1 (800) 543-8630 +1 (215) 619-2700

©2026 C&D Technologies Inc. Any data, descriptions or specifications presented herein are subject to revision by C&D Technologies, Inc. without notice. While such information is believed to be accurate as indicated herein, C&D Technologies, Inc. makes no warranty and hereby disclaims all warranties, express or implied, with regard to the accuracy or completeness of such information. Further, because the product(s) featured herein may be used under conditions beyond its control, C&D Technologies, Inc. hereby disclaims all warranties, either express or implied, concerning the fitness or suitability of such product(s) for any particular use or in any specific application or arising from any course of dealing or usage of trade. The user is solely responsible for determining the suitability of the product(s) featured herein for user's intended purpose and in user's specific application.



200 Precision Drive, Suite 150 Horsham, Pennsylvania 19044 USA | [www.cdtechno.com](http://www.cdtechno.com)

