



FPLR Riser Shld

Riser (PVC) Fire Alarm Cable (FPLR) is used for fire protective systems including burglar alarms and smoke detectors. Shielding provides extra protection from electrostatic noise and cross talk.

Voltage: 300V

Conductor: Twisted solid bare copper

Shield: Overall foil shield

Insulation: PVC with FPLR rating

Jacket: PVC with FPLR rating ripcord for easy stripping

Flame Test: UL 1666

Color Code: [Click here](#)

DWC Part #	AWG Size	# of Conductors	# of Strands	Insulation Thickness In Mils	Jacket Thickness In Mils	O.D. Inch	Weight Lbs/M
1802SFPLR	18	2	solid	10	15	0.16	21
1804SFPLR	18	4	solid	10	15	0.18	33
1806SFPLR	18	6	solid	10	15	0.22	48
1808SFPLR	18	8	solid	10	15	0.24	61
1602SFPLR	16	2	solid	10	15	0.18	28
1604SFPLR	16	4	solid	10	15	0.21	47
1402SFPLR	14	2	solid	10	15	0.22	44
1404SFPLR	14	4	solid	10	15	0.25	75
1202SFPLR	12	2	solid	10	15	0.25	62

Product details and specifications are subject to manufacturing variations and accepted industry tolerances. Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.

fastQuote™