



Jumper Cable

5/15KV Jumper cable is used for temporary power supply ranging from 5000 volts to 15000 volts. It is rated for -40C to 90C.

Extra flexible copper

Insulation: Ethylene propylene rubber (EPR)

Jacket: Red Chlorinated Polyethylene (CPE)

| DWC Part # | AWG Size | # of Strands | Conductor O.D. Inch | Insulation Thickness In Mils | Jacket Thickness In Mils | O.D. Inch | Weight Lbs/M |
|----------------|----------|--------------|---------------------|------------------------------|--------------------------|-----------|--------------|
| 0201515KVJump | 2 | 259 | 0.33 | 210 | 65 | 0.91 | 550 |
| 0101515KVJump | 1 | 259 | 0.38 | 210 | 65 | 0.95 | 630 |
| 1/001515KVJump | 1/0 | 266 | 0.42 | 210 | 65 | 1 | 726 |
| 2/001515KVJump | 2/0 | 342 | 0.47 | 210 | 65 | 1.05 | 855 |
| 4/001515KVJump | 4/0 | 532 | 0.6 | 210 | 65 | 1.16 | 1165 |
| 35001515KVJump | 350 | 888 | 0.78 | 210 | 65 | 1.3 | 1685 |
| 50001515KVJump | 500 | 1221 | 0.93 | 210 | 65 | 1.43 | 2185 |

Product details and specifications are subject to manufacturing variations and accepted industry tolerances.

Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.

fastQuote™