



CMR Riser Shld

Application: Low voltage riser PVC (CMR) cables are used in various applications such as sound, security and PA systems.

The overall shield provides additional protection from electrostatic noise and crosstalk. Rated for 300V.

Conductor: Stranded bare copper

Insulation: PVC with CMR rating

Shield: Overall foil shield

Jacket: PVC with CMR rating

Flame Test: UL Flame Test (1666)

Note: 22 AWG -16 AWG rated CMR | 14 AWG – 12 AWG rated CL3R

Color Code: [Click here](#)

DWC Part #	AWG Size	# of Conductors	# of Strands	Insulation Thickness In Mils	Jacket Thickness In Mils	O.D. Inch	Weight Lbs/M
2202SCMR	22	2	7	8	15	0.13	12
2203SCMR	22	3	7	8	15	0.14	16
2204SCMR	22	4	7	8	15	0.15	20
2206SCMR	22	6	7	8	15	0.17	26
2208SCMR	22	8	7	8	15	0.2	31
2212SCMR	22	12	7	8	15	0.23	42
2002SCMR	20	2	7	8	15	0.15	17
2003SCMR	20	3	7	8	15	0.15	21
2004SCMR	20	4	7	8	15	0.17	25
1802SCMR	18	2	7	9	15	0.16	21
1803SCMR	18	3	7	9	15	0.17	28
1804SCMR	18	4	7	9	15	0.19	35
1806SCMR	18	6	7	9	15	0.23	50
1808SCMR	18	8	7	9	15	0.25	63
1812SCMR	18	12	7	9	15	0.3	90
1602SCMR	16	2	19	9	15	0.19	29
1603SCMR	16	3	19	9	15	0.2	39
1604SCMR	16	4	19	9	15	0.22	50
1402SCMR	14	2	19	13	15	0.25	46
1403SCMR	14	3	19	13	15	0.25	61
1404SCMR	14	4	19	13	15	0.27	79
1202SCMR	12	2	19	13	15	0.3	75

Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.