



## Type W Single Conductor

Type W is a 2KV (2000 volts) portable/mining cord frequently used in industrial mining applications and heavy duty service for power supply where high flexibility is needed.

**Conductor:** Extra flexible bare copper

**Insulation:** Ethylene propylene diene monomer (EPDM)

**Jacket:** CPE

**Notes:** MSHA Approved

DWC Part #	AWG Size	# of Strands	Insulation Thickness In Mils	Jacket Thickness In Mils	O.D. Inch	Weight Lbs/M
0801W	8	133	60	75	0.44	155
0601W	6	266	60	95	0.53	267
0401W	4	259	60	95	0.6	369
0201W	2	259	60	95	0.66	458
0101W	1	259	80	95	0.74	475
1/001W	1/0	259	80	95	0.79	658
2/001W	2/0	259	80	95	0.81	730
3/001W	3/0	259	80	95	0.91	805
4/001W	4/0	259	80	95	0.95	1049
25001W	250	627	95	95	1.08	1425
35001W	350	855	95	95	1.2	1971
50001W	500	1235	95	95	1.34	2651

*Product details and specifications are subject to manufacturing variations and accepted industry tolerances. Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.*

**fastQuote™**