



## XHHW

XHHW is a general purpose building wire. Approved to use in circuits not exceeding 600 volts. Highly resistant to chemicals, ozone and abrasion. VW-1 rated cables are suitable when the vertical wire flame test is required. This item is sunlight resistant. 1/0 and larger are CT(cable tray) rated.

**Conductor:** Bare Copper

**Insulation:** Cross-linked polyethylene (XLP)

**Flame Test:** UL and IEEE 383 70,000 BTU/hr flame test. UL VW-1.

**Note:** Available in multiple colors

DWC Part #	AWG Size	# of Strands	Insulation Thickness In Mils	O.D. Inch	Weight Lbs/M
1401XHHW	14	7	30	0.14	18
1201XHHW	12	7	30	0.16	27
1001XHHW	10	7	30	0.18	40
0801XHHW	8	7	45	0.24	66
0601XHHW	6	7	45	0.28	97
0401XHHW	4	7	45	0.32	145
0201XHHW	2	7	45	0.38	225
0101XHHW	1	19	55	0.44	290
1/001XHHW	1/0	19	55	0.48	360
2/001XHHW	2/0	19	55	0.52	450
3/001XHHW	3/0	19	55	0.58	565
4/001XHHW	4/0	19	55	0.63	705
25001XHHW	250	37	65	0.7	835
35001XHHW	350	37	65	0.8	1155
50001XHHW	500	37	65	0.93	1630
60001XHHW	600	37	65	1.026	1950
75001XHHW	750	61	80	1.14	2445
100001XHHW	1000	61	80	1.29	3230

*Product details and specifications are subject to manufacturing variations and accepted industry tolerances. Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.*

**fastQuote™**