



## Category 3 Phone Cable – PVC/Plenum

Category 3 cable is designed to carry data up to 10 Mbit/s with a max bandwidth of 16 MHz. This item can be used indoor/outdoor in conduit but not direct buried.

**Conductor:** Solid bare copper with each individual pair twisted together

**Insulation:** CMR – riser rated or CMP – plenum rated.

**Jacket:** CMR (riser) or CMP (plenum)

**Color Code:** [Click here](#)

DWC Part #	AWG Size	# of Pairs	O.D. Inch	Weight Lbs/M
2402PCMP3	24	2	0.14	10
2402PCMR3	24	2	0.12	9
2403PCMP3	24	3	0.15	15
2403PCMR3	24	3	0.14	12
2404PCMP3	24	4	0.17	18
2404PCMR3	24	4	0.16	15
2406PCMP3	24	6	0.2	24
2406PCMR3	24	6	0.19	22
24100PCMP3	24	100	0.77	377
24100PCMR3	24	100	0.64	308
2412PCMP3	24	12	0.28	53
2412PCMR3	24	12	0.24	41
24200PCMP3	24	200	1.1	728
24200PCMR3	24	200	0.85	724
2425PCMP3	24	25	0.4	106
2425PCMR3	24	25	0.33	80
2450PCMP3	24	50	0.56	191
2450PCMR3	24	50	0.47	160

*Product details and specifications are subject to manufacturing variations and accepted industry tolerances.  
Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.*

**fastQuote™**