



Type G

Type G is a 2KV (2000 volts) portable/mining cord frequently used in industrial mining applications and heavy duty service for power supply where high flexibility is needed. Used in three-phase AC systems where grounding is required.

Conductor: Extra flexible bare copper

Insulation: Ethylene propylene diene monomer (EPDM)

Grounds: Four ground conductors (all insulated and color coded)

Jacket: CPE

Notes: MSHA Approved

Color Code: Black, white, red and orange

DWC Part #	AWG Size	# of Strands	Insulation Thickness In Mils	Grounding Conductor AWG	O.D. Inch	Weight Lbs/M
0804G	8	133	60	4 # 12	1.02	829
0604G	6	133	60	4 # 12	1.13	1046
0404G	4	133	60	4 # 10	1.24	1363
0304G	3	133	60	4 # 10	1.31	1550
0204G	2	133	60	4 # 9	1.4	1802
0104G	1	133	80	4 # 8	1.64	2620
1/004G	1/0	259	80	4 # 7	1.77	3163
2/004G	2/0	259	80	4 # 6	1.91	3546
3/004G	3/0	259	80	4 # 5	2.05	4360
4/004G	4/0	259	80	4 # 4	2.24	5269
25004G	250	627	95	4 # 3	2.65	6060
35004G	350	888	95	4 # 1	2.98	8130
50004G	500	1221	95	4 # 1/0	3.4	10765

Product details and specifications are subject to manufacturing variations and accepted industry tolerances. Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.

fastQuote™