



## FPLP Plenum Shld

Plenum Fire Alarm Cable (FPLP) is used for fire protective systems including burglar alarms and smoke detectors where a plenum rating is required. Shielding provides extra protection from electrostatic noise and cross talk.

**Voltage:** 300V

**Jacket:** Low smoke PVC with FPLP rating ripcord for easy stripping

**Flame Test:** Steiner Tunner Flame Test (UL 910)

**Color Code:** [Click here](#)

DWC Part #	AWG Size	# of Conductors	# of Strands	Insulation Thickness In Mils	Jacket Thickness In Mils	O.D. Inch	Weight Lbs/M
1802SFPLP	18	2	solid	10	15	0.16	21
1804SFPLP	18	4	solid	10	15	0.18	35
1806SFPLP	18	6	solid	10	15	0.22	50
1808SFPLP	18	8	solid	10	15	0.23	63
1602SFPLP	16	2	solid	10	15	0.18	29
1604SFPLP	16	4	solid	10	15	0.21	49
1402SFPLP	14	2	solid	12	15	0.21	45
1404SFPLP	14	4	solid	12	15	0.25	76
1202SFPLP	12	2	solid	13	15	0.25	62

*Product details and specifications are subject to manufacturing variations and accepted industry tolerances. Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.*

**fastQuote™**