



SOOW – 10 AWG

SOOW portable cord is used on industrial and processing equipment, cranes and hoist, motors and other equipment when flexibility and resistance to solvents, oils, flame and moisture are required. Suitable for shallow/medium water immersion. This product is rated for 600V and 90C.

Conductor: Stranded bare copper

Insulation: Thermoplastic elastomer

Jacket: CPE

Notes: MSHA approved for hard usage

Color Code: [Click Here](#)

DWC Part #	AWG Size	# of Conductors	# of Strands	Insulation Thickness In Mils	Jacket Thickness In Mils	O.D. Inch	Weight Lbs/M
1002SOOW	10	2	104	45	95	0.62	215
1003SOOW	10	3	104	45	95	0.66	290
1004SOOW	10	4	104	45	95	0.71	350
1005SOOW	10	5	104	45	95	0.77	465
1006SOOW	10	6	104	45	95	0.87	490
1007SOOW	10	7	104	45	95	0.89	500
1008SOOW	10	8	104	45	95	0.94	625
1010SOOW	10	10	104	45	110	1.02	765
1012SOOW	10	12	104	45	110	1.07	865
1016SOOW	10	16	104	45	125	1.23	1150
1020SOOW	10	20	104	45	125	1.26	1445

Product details and specifications are subject to manufacturing variations and accepted industry tolerances. Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.

fastQuote™