



CMP Plenum Non-Shld

Low voltage plenum (CMP) cables are used in drop ceilings for sound, security, PA and fire alarm systems with the FPLP rating.

Conductor: Stranded bare copper

Flame Test: Steiner Tunner Flame Test (UL 910)

Note: 22 AWG -16 AWG rated CMP | 14 AWG – 12 AWG rated CL3P

Color Code: [Click here](#)

DWC Part #	AWG Size	# of Conductors	# of Strands	Insulation Thickness In Mils	Jacket Thickness In Mils	O.D. Inch	Weight Lbs/M
2202CMP	22	2	7	8	15	0.12	12
2203CMP	22	3	7	8	15	0.13	14
2204CMP	22	4	7	8	15	0.14	19
2206CMP	22	6	7	8	15	0.16	24
2208CMP	22	8	7	8	15	0.18	30
2212CMP	22	12	7	8	15	0.22	43
2002CMP	20	2	7	8	15	0.14	16
2003CMP	20	3	7	8	15	0.15	20
2004CMP	20	4	7	8	15	0.16	25
2008CMP	20	8	7	8	15	0.21	42
2012CMP	20	12	7	8	15	0.25	61
1802CMP	18	2	7	8	15	0.16	18
1803CMP	18	3	7	8	15	0.17	25
1804CMP	18	4	7	8	15	0.19	30
1806CMP	18	6	7	8	15	0.22	48
1808CMP	18	8	7	8	15	0.25	61
1812CMP	18	12	7	8	15	0.29	91
1602CMP	16	2	19	8	15	0.17	26
1603CMP	16	3	19	8	15	0.19	36
1604CMP	16	4	19	8	15	0.2	46
1606CMP	16	6	19	8	15	0.25	46
1608CMP	16	8	19	8	15	0.34	62
1402CMP	14	2	19	8	15	0.22	42
1403CMP	14	3	19	8	15	0.24	60
1404CMP	14	4	19	8	15	0.26	78
1202CMP	12	2	19	8	15	0.26	60
1204CMP	12	4	19	8	15	0.38	95

*Product details and specifications are subject to manufacturing variations and accepted industry tolerances.
Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.*