



TECK 14 AWG – 10 AWG

Teck 90 or Teck Style armored cables are used in industrial and commercial applications where the environment requires extra protection or durability. These cables can be direct buried and installed in conduit. HL (Hazardous Location) rated.

Rated for 600/1000 volts and 90C.

Conductor: Stranded bare copper

Insulation: XLP

Armor: Aluminum interlocked armor

Jacket: Inner and Outer PVC

Flame Test: UL 1581 70,000 BTU/hour flame test

Color Code: 2 Conductor: black, white – 3 Conductor: black, red, blue – 4 Conductor: black, red, blue, white – 5 Conductor and up: black with printed numbers.

DWC Part #	AWG Size	# of Conductors	Voltage	Insulation Thickness In Mils	Ground Wire AWG	Armor O.D. Inch	O.D. Inch	Weight Lbs/M
1402TECK	14	2	600	30	14	0.58	0.67	195
1403TECK	14	3	600	30	14	0.62	0.71	255
1404TECK	14	4	600	30	14	0.67	0.76	266
1405TECK	14	5	600	30	14	0.7	0.79	321
1407TECK	14	7	600	30	14	0.76	0.85	345
1410TECK	14	10	600	30	14	0.88	0.96	451
1412TECK	14	12	600	30	14	0.9	0.99	511
1415TECK	14	15	600	30	14	0.96	1.04	586
1420TECK	14	20	600	30	14	1.13	1.21	789
1425TECK	14	25	600	30	14	1.22	1.3	958
1202TECK	12	2	600	30	14	0.62	0.7	228
1203TECK	12	3	600	30	14	0.66	0.75	280
1204TECK	12	4	600	30	14	0.73	0.82	341
1205TECK	12	5	600	30	14	0.77	0.86	372
1207TECK	12	7	600	30	14	0.83	0.91	443
1212TECK	12	12	600	30	14	1.01	1.1	850
1215TECK	12	15	600	30	14	1.14	1.23	972
1220TECK	12	20	600	30	14	1.23	1.32	1050
1225TECK	12	25	600	30	14	1.35	1.44	1164
1002TECK	10	2	600	30	12	0.67	0.75	275
1003TECK	10	3	600	30	12	0.71	0.8	339
1004TECK	10	4	600	30	12	0.78	0.87	400
1005TECK	10	5	600	30	12	0.83	0.92	472
1006TECK	10	6	600	30	12	0.88	0.96	532
1007TECK	10	7	600	30	12	0.92	1.01	539
1008TECK	10	8	600	30	12	0.93	1.02	791
1012TECK	10	12	600	30	12	1.17	1.26	885

*Product details and specifications are subject to manufacturing variations and accepted industry tolerances.
Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.*

fastQuote™

☎ 888.439.2947

🌐 distributorwire.com

📠 720.317.2278