



## TGGT

TGGT (TFE Teflon) is used in high temperature applications up to 250C for commercial or industrial heating equipment. It uses a flex stranding with a VW-1 rating. 600V.

**Conductor:** Nickel plated copper

**Insulation:** TFE Teflon with fiberglass serve

**Jacket:** Impregnated glass braid

**Notes:** Standard color is natural/tan

DWC Part #	AWG Size	# of Strands	Insulation Thickness In Mils	Jacket Thickness In Mils	Serve Thickness In Mils	O.D. Inch	Weight Lbs/M
1801TGGT	18	16	15	13	10	0.11	13
1601TGGT	16	26	15	13	10	0.12	18
1401TGGT	14	41	15	13	10	0.14	24
1201TGGT	12	65	15	13	10	0.16	34
1001TGGT	10	105	15	13	10	0.19	51
0801TGGT	8	133	15	13	10	0.23	65
0601TGGT	6	133	20	19	15	0.29	114
0401TGGT	4	133	20	19	15	0.34	168
0201TGGT	2	133	20	19	15	0.41	246
1/001TGGT	1/0	259	35	19	15	0.51	392
2/001TGGT	2/0	259	35	19	15	0.57	490
4/001TGGT	4/0	259	35	19	15	0.69	746

*Product details and specifications are subject to manufacturing variations and accepted industry tolerances. Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.*

**fastQuote™**