



## SJOOW

SJOOW portable cord is used on industrial and processing equipment, cranes and hoist, motors and other equipment when flexibility and resistance to solvents, oils, flame and moisture are required. Suitable for shallow/medium water immersion. This junior service cord is rated for 300V and 90C.

**Conductor:** nStranded bare copper

**Insulation:** nThermoplastic elastomer

**Jacket:** CPE

**Color Code:**

2 Conductors: Black, White

3 Conductors: Black, White, Green

4 Conductors: Black, White, Red, Green

DWC Part #	AWG Size	# of Conductors	# of Strands	Insulation Thickness in Mils	Jacket Thickness in Mils	O.D. Inch	Weight Lbs/M
1802SJOOW	18	2	16	0.76	0.76	0.28	42
1803SJOOW	18	3	16	0.76	0.76	0.28	52
1804SJOOW	18	4	16	0.76	0.76	0.28	63
1602SJOOW	16	2	26	0.76	0.76	0.33	53
1603SJOOW	16	3	26	0.76	0.76	0.36	66
1604SJOOW	16	4	26	0.76	0.76	0.36	83
1402SJOOW	14	2	41	0.76	0.76	0.34	68
1403SJOOW	14	3	41	0.76	0.76	0.36	88
1404SJOOW	14	4	41	0.76	0.76	0.4	110
1202SJOOW	12	2	65	0.76	1.14	0.41	104
1203SJOOW	12	3	65	0.76	1.14	0.43	131
1204SJOOW	12	4	65	0.76	1.14	0.47	163
1002SJOOW	10	2	103	1.14	1.52	0.54	177
1003SJOOW	10	3	103	1.14	1.52	0.58	225
1004SJOOW	10	4	103	1.14	1.52	0.63	279

*Product details and specifications are subject to manufacturing variations and accepted industry tolerances. Please contact your DWC Account Manager with questions, or to confirm any specific product requirements.*

**fastQuote™**